

### 6Pc. Automotive Body Repair Tool Set

Cat. No.	0	2	G.W.
09152			14.6 kg


- CONTENTS:**
- 1 - Anvil Dolly
  - 1 - Wedge Dolly
  - 1 - Pry Bumping Spoon
  - 1 - Toe Dolly
  - 1 - Light Shrinking Hammer
  - 1 - Pick & Finishing Hammer



### 14 Pc. Feeler Gauge Set 0.05-1.00mm

Cat. No.	0	144	G.W.
09401	24		12.1 kg

- CONTENTS:**
- 0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.00mm



- Meet DIN2275 & JIS B 7524-1992 standard
- Blade length 3"
- Blade is made of 65#Mn polished steel

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 32 Pc. Feeler Gauge Set 0.02-1.00mm

Cat. No.	0	144	G.W.
09407	24		20.7 kg

- CONTENTS:**
- 0.02, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.13, 0.15, 0.18, 0.20, 0.23, 0.25, 0.28, 0.30, 0.33, 0.38, 0.40, 0.45, 0.50, 0.55, 0.60, 0.63, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 1.00mm



- Meet DIN2275 & JIS B 7524-1992 standard
- Blade length 3.5"
- Blade is made of 65#Mn polished steel

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 8 Pc. End Cap Oil Filter Wrench Set

Cat. No.	0	4	G.W.
09703			10.8 kg

- CONTENTS:**
- 6 - 3/8" Dr. End Cap Oil Filter Wrenches  
65, 74, 76, 80, 90, 93 mm
  - 1 - 3/8" Dr. Quick-Release Ratchet
  - 1 - 1/2" F x 3/8" M Socket Adapter



- Caution: Do not use with power tools
- Specially designed wrench removes and installs hard-to-reach oil filters

### 16 Pc. Feeler Gauge Set 0.05-1.00mm

Cat. No.	0	144	G.W.
09402	12		17.4 kg

- CONTENTS:**
- 0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.50, 0.55, 0.60, 0.70, 0.75, 0.80, 0.90, 1.00mm



- Meet DIN2275 & JIS B 7524-1992 standard
- Blade length 3"
- Blade is made of 65#Mn polished steel

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 23 Pc. Feeler Gauge Set 0.02-1.00mm

Cat. No.	0	144	G.W.
09405	36		16.6 kg

- CONTENTS:**
- 0.02, 0.03, 0.04, 0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00mm



- Meet DIN2275 & JIS B 7524-1992 standard
- Blade length 4"
- Blade is made of 65#Mn polished steel

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 50 Pc. Automotive Tool Set

Cat. No.	0	2	G.W.
09508			19 kg

- CONTENTS:**
- 11 - 1/2" Dr. 12pt. Metric Sockets 8, 10, 12, 17, 18, 19, 20, 21, 22, 24, 27 mm
  - 1 - 1/2" Dr. 50L Bit Socket Hex 17 mm
  - 1 - 1/2" Dr. 100L Bit Socket Hex 7 mm
  - 9 - 1/2" Dr. Extra Long Bit Sockets  
Hex 6x70, 6x120, 6x250, 5x180, 6x140, 10x140 mm  
Triple Square M8x100, M10x120, M10x140 mm
  - 9 - Extra Long Arm Ball Point Hex Key Set 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm
  - 2 - 1/2" Dr. Spark Plug Sockets 16, 21 mm
  - 2 - Cushion Grip Go-Through Screwdrivers  
Slotted 6x100 mm  
Phillips #6x100 mm
  - 15 - Accessories  
1/2" Dr. Quick-Release Ratchet  
1/2" Dr. T-handle  
1/2" Dr. Wobble Extensions 5", 10"  
1/2" Dr. Universal Joint  
1/2" Dr. Offset Handle 260mm  
3/8" Dr. Two Way Oil Filter Wrench with Adapter  
Raised Panel Combination Wrenches 8, 10, 13, 17, 18, 22 mm  
Front Shock Absorption Install Tool  
Shock Absorption Install Socket



### 56 Pc. Automotive Tool Set

Cat. No.	0	4	G.W.
09509			20.2 kg

**CONTENTS:**

- 15 - 3/8" Dr. 6pt. Metric Sockets  
7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24 mm
- 15 - 1/4" Shank 25L Bits  
Slotted 4, 5, 6.5 mm  
Phillips #1, #3 Hex 3, 4, 5, 6 mm  
Tamper Torx® T10, T15, T20, T25, T30, T40
- 2 - 3/8" Dr. Spark Plug Sockets 16, 21 mm
- 2 - Cushion Grip Go-Through Screwdrivers  
Slotted 6x100 mm  
Phillips #2x100 mm
- 22 - Accessories  
1/4" Dr. Spinner Handle  
1/4" Dr. Adapter  
1/4" Dr. x 1/4" Shank Bit Adapter  
3/8" Dr. Quick-Release Ratchet  
3/8" Dr. Wobble Extensions 3", 10"  
3/8" Dr. Universal Joint  
3/8" Dr. Adapter  
1/2" Dr. 3-Way Adapter  
Combination Wrenches 8, 10, 12, 13, 14, 15, 16, 17, 18, 19, 22 mm  
Long Nose Pliers 6"  
Slip Joint Pliers 8"



### 5 Pc. Fine Threaded Extractor Set

Cat. No.	6	72	G.W.
09704			11.1 kg

**CONTENTS:**

- 2, 3, 4, 6.5, 7mm



- For removing screws and studs that cannot be held firmly
- Made from hardened and tempered steel(Cr-Mn)
- Tapered extractors for broken screws and studs

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 5 Pc. Coarse Threaded Extractor Set

Cat. No.	6	72	G.W.
09704A			11.1 kg

**CONTENTS:**

- 3.3, 5.3, 6.4, 8.8, 11.2mm



- Coarse thread design for longer usage life
- Easy to use for quick removing broken screws
- Selection of GCr15 bearing steel materials. Hardness can reach HRC58-60

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 5 Pc. Hook and Pick Set

Cat. No.	20	200	G.W.
09709			11 kg



- It's convenient to work on O-rings, seals and split pins etc.
- Heat-treated to improve durability
- Includes a piece of Magnetic extra long handle

### Cross Wheel Wrench

Cat. No.	Size	4	12	G.W.
48101	17, 19, 21mm, 1/2 in			17 kg



- Made of Chrome Vanadium steel
- ⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### Digital Circuit Tester

Cat. No.	24	240	G.W.
62601			9.8 kg



- Do not use as normal screwdrivers
- Do not test on 360 Voltage electric sources
- Direct on in-direct measure for 12, 36, 55, 110 and 220 Voltage(AC & DC)
- Induction test for easy break-point test, microwave radiation and leakage conditions
- LCD digital display
- No battery required

**⚠ Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.**

### 2-Jaw Gear Pullers

Cat. No.	Size	Overall Length	Jaw Capacity	0	48	G.W.
90623	3 in	125 mm	75 mm			20.2 kg
90624	4 in	155 mm	100 mm		24	20.2 kg
90626	6 in	240 mm	150 mm		12	21.4 kg
90628	8 in	325 mm	200 mm		5	19 kg



- Slip-resistant jaws design
- The shaft tip has gone through special heat treatment to increase durability

### 3-Jaw Gear Pullers

Cat. No.	Size	Overall Length	Jaw Capacity			G.W.
90633	3 in	125 mm	75 mm	0	24	14.5 kg
90634	4 in	155 mm	100 mm	0	18	20.1 kg
90636	6 in	240 mm	150 mm	0	8	20.9 kg
90638	8 in	325 mm	200 mm	0	4	21.6 kg
90640	10 in	340 mm	250 mm	0	3	25 kg
90642	12 in	385 mm	300 mm	0	2	22 kg



- Slip-resistant jaws design
- The shaft tip has gone through special heat treatment to increase durability

### Universal Ball Joint Separator

Cat. No.			G.W.
90651	0	18	19 kg



- Made of Chrome Vanadium steel with special heat treatment
- For separating ball joints

### Outer Tie Rod Remover

Cat. No.			G.W.
90661	0	18	14.5 kg
90662	6	12	14 kg



- Slip-resistant jaws design
- High quality screws to ensure maximum Torque
- Made of Chrome Vanadium steel with special heat treatment
- For separating ball joints

### Anvil Dolly

Cat. No.			G.W.
92203	6	12	17 kg



- Made of high carbon steel by forging and tempering, boosting strength and durability

### Wedge Dolly

Cat. No.			G.W.
92205	6	12	20.5 kg



- Made of high carbon steel by forging and tempering, boosting strength and durability

### Ball Joint Separator 12"

Cat. No.			G.W.
90665	6	24	19.3 kg



- Powerful tool for separating ball joint.
- To insert the tool to appropriate place and knock with a hammer to separate the ball joint.
- It can withstand strong knocking

### Toe Dolly

Cat. No.			G.W.
92207	6	12	18 kg



- Made of high carbon steel by forging and tempering, boosting strength and durability

### Pry Bumping Spoon

Cat. No.			G.W.
92209	0	12	17 kg



- Made of high carbon steel by forging and tempering, boosting strength and durability

### Wood Handle Putty Scraper

Cat. No.			G.W.
95201	6	60	8.4 kg



- Can be used for cleaning dirt on engine cylinder surface and all kind of metal surface
- Wood handle provides more comfortable
- Heavy Duty edge

Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### Rigid Scraper

Cat. No.			G.W.
97105	12	72	15.5 kg



- Scrapes surfaces clean for installing new gaskets

Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### Grease Gun Coupler

Cat. No.			G.W.
97211	18	72	3.3 kg



- Nozzle with ball-bearing ensures no reverses flow

Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### Flexible Whip Hose

Cat. No.	Overall		⊞	⊞	G.W.
	Length				
97212	300 mm	9	72		7.2 kg
97213	450 mm	9	72		9.6 kg



- High-strength pressure nylon hose can easily insert the work area.

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### Universal 3-Jaw Oil Filter Wrench

Cat. No.	Max	Min	⊞	⊞	G.W.
	Diameter	Diameter			
97422	102 mm	63 mm	2	16	7.8 kg



- Torque output increased by 10%
- Works with 1/2" and 3/8" drive tools.
- Two-way action installs or removes filters

### 1/2" Drive Oil Filter Strap Wrench

Cat. No.	Max	⊞	⊞	G.W.
	Diameter			
97441	120 mm	4	32	7 kg



- The strong and durable nylon belt can work in confined space
- It can demount oil filters with a diameter below 120mm
- It can work with 1/2" drive tools and 13/16" spinner handles

### End Cap Oil Filter Wrenches

Cat. No.	Max	Min	⊞	⊞	G.W.
	Diameter	Diameter			
97401	65 mm	65 mm	4	32	6 kg
97403	74 mm	74 mm	4	32	6.4 kg
97404	76 mm	76 mm	4	32	6.4 kg
97405	80 mm	80 mm	4	32	6.8 kg
97406	90 mm	90 mm	4	32	6.8 kg
97407	93 mm	93 mm	4	32	6.8 kg



- Works with 3/8" DR. or 1/2" DR drive tools.
- Special design with Chromate treatment

### Adjustable Oil Filter Wrench Pliers

Cat. No.	Max	Min	⊞	⊞	G.W.
	Diameter	Diameter			
97426	116 mm	63.5 mm	6	36	17.5 kg



- Plastic wrapped handle provides comfortable grip
- Two clamp handle allows larger clamping power.
- For removing 63.5-116mm oil filters

### Piston Ring Compressor

Cat. No.	Size	⊞	⊞	G.W.
97501	3 in	30	60	18.5 kg
97502	4 in	30	60	20.5 kg

- Working range:
- 97501 53-175MM
- 97502 60-175MM
- Tool is beaded along lower edge to prevent compressor from entering the cylinder
- Heavy spring steel compresses the stiffest rings evenly
- Positive lock action provides positive compression and fingertip release

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Valve Seal Removal Pliers

Cat. No.	⊞	⊞	G.W.
97511	6	48	19.7 kg

- For mounting and dismounting valve seals and springs



### Electrical Wire Stripper and Crimper

Cat. No.	⊞	⊞	G.W.
97521	6	72	17.3 kg

- Multi-purpose usage:
- Clamp
- Insulated crimping pliers
- Wire stripper(0.75-6MM)
- Non-insulated crimping pliers
- Cable cutter 7-8MM
- Auto crimping pliers
- Bolt cutter M2.6-M5



### Drop Forged Coil Spring Compressor

Cat. No.	Size	⊞	⊞	G.W.
97701	270 mm	0	8	14.9 kg
97702	370 mm	0	8	17.1 kg

- Size:
- 97701: 270 mm
- 97702: 370 mm
- Special reinforced screw thread design to ensure safety
- Suitable for use where space under wheel arch is limited
- Works with 1/2" drive tools and 21mm sockets and wrenches Made of quality carbon steel



### Scissor Jack

Cat. No.	Maximum		⊞	⊞	G.W.
	Load				
97831	1.5 T	0	10		33 kg

- Supplied complete with cranking handle
- Lifting range 95-350mm

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Hand-Operated Pistol Grip Grease Gun 100CC

Cat. No.	☐	☒	G.W.
97201	1	12	5.55 kg

- Suitable for: standard pack oil, seal oil can, 100CC bulk oil
- High strength pressure zinc alloy steel cast tip
- High strength heat-treated spring to ensure the pressure lasting and balance
- Special self-lock device for more safety and convenience
- Special design to add a steel ball inside to ensure the oil does not reflow
- Grease gun highest pressure 4500 PSI(315KGF/CM2) For cars, trucks, tractors, boats, road rollers, harvesters and large construction machinery

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Hand-Operated Grease Gun 400CC

Cat. No.	☐	☒	G.W.
97202	1	12	9.5 kg

- Suitable for: standard 140Z pack oil, seal oil can, 400CC bulk oil
- High strength pressure zinc alloy steel cast tip
- High strength heat-treated spring to ensure the pressure lasting and balance
- Special self-lock device for more safety and convenience
- Special design to add a steel ball inside to ensure the oil does not reflow
- Grease gun highest pressure 10000PSI(700KGF/CM2)
- For cars, trucks, tractors, boats, road rollers, harvesters and large construction machinery

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Hand-Operated Plastic Handle Grease Gun 400CC

Cat. No.	☐	☒	G.W.
97203	1	12	9.5 kg

- Suitable for: standard 140Z pack oil, seal oil can, 400CC bulk oil
- High strength pressure zinc alloy steel cast tip
- High strength heat-treated spring to ensure the pressure lasting and balance
- Special self-lock device for more safety and convenience
- Special design to add a steel ball inside to ensure the oil does not reflow
- Grease gun highest pressure 10000PSI(700KGF/CM2)
- For cars, trucks, tractors, boats, road rollers, harvesters and large construction machinery

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Hand-Operated Heavy Duty Grease Gun 600CC

Cat. No.	☐	☒	G.W.
97204	1	10	17.4 kg

- High strength cast iron gun tip for high pressure and high capacity
- Design for construction machinery and heavy duty machinery
- With taper nozzle for grease gun for special occasions refueling
- Can hold grease
- For excavators, loaders, graders, rollers, pavers and cranes and other machinery and equipment

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Hand-Operated High Pressure Grease Gun 400CC

Cat. No.	☐	☒	G.W.
97205	1	12	7.9 kg

- Unique high and low pressure switch button for easy and convenient operation
- Patent loop exhaust mouth to ensure the grease gun work smoothly
- Patent big small shaft design to switch high and low pressure for refueling
- Unique square tooth veins design to ensure the convenience of equip gun tip and gun barrel
- Removable rear cover for easy cleaning barrel
- heavy duty thicken handle design for bearing higher operating force

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Heavy Duty Service Jack 2.5 Ton

Cat. No.	Maximum Load	☐	☒	G.W.
97813	2.5 T	0	1	315 kg

- Ensure nominal deadweight achieve marked value to ensure the use safety
- Each one have been through 1.5 times tonnage overload test and passed the test before leaving the factory to ensure sufficient loading safety factor
- The valve will automatically open and unloading automatically when loading weight reach to 1.1 times tonnage setting to ensure the safety
- Ultralow design can lift low chassis sports car
- Universal joint Steering mechanism for more durability
- Double oil line hydraulic pump for fast lifting
- Meet ASME PALD-2009
- Pedal design for easy operation and save effort
- Patent design dual handles for easy moving Service Jack

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Heavy Duty Low Profile Service Jack 1.5 Ton

Cat. No.	Maximum Load	☐	☒	G.W.
97816	1.5 T	0	1	46 kg

- Ensure nominal deadweight achieve marked value to ensure the use safety
- Each one have been through 1.5 times tonnage overload test and passed the test before leaving the factory to ensure sufficient loading safety factor
- The valve will automatically open and unload automatically when loading weight reach to 1.1 times tonnage setting to ensure safety
- Ultralow design can lift low chassis sports car
- Universal joint Steering mechanism for more durability
- Double oil line hydraulic pump for fast lifting
- Meet ASME PALD-2009 Pedal design for easy operation and save effort
- Patent design dual handles for easy moving Service Jack

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.



### Heavy Duty Low Profile Service Jack 2 Ton

Cat. No.	Maximum Load			G.W.
97817	2 T	0	1	34 kg

- Ensure nominal deadweight achieve marked value to ensure the use safety
- Each one have been through 1.5 times tonnage overload test and passed the test before leaving the factory to ensure sufficient loading safety factor
- The valve will automatically open and unload automatically when loading weight reach to 1.1 times tonnage setting to ensure safety
- Ultralow design can lift low chassis sports car
- Universal joint Steering mechanism for more durability
- Double oil line hydraulic pump for fast lifting
  - Meet ASME PALD-2009
- Pedal design for easy operation and save effort.
- Patent design dual handles for easy moving Service Jack

Nature of this product is subject to wear and tear upon usage.  
Not covered under Lifetime Warranty.



### Heavy Duty Low Profile Service Jack 3 Ton

Cat. No.	Maximum Load			G.W.
97818	3 T	0	1	46.5 kg

- Ensure nominal deadweight achieve marked value to ensure the use safety
- Each one have been through 1.5 times tonnage overload test and passed the test before leaving the factory to ensure sufficient loading safety factor
- The valve will automatically open and unload automatically when loading weight reach to 1.1 times tonnage setting to ensure safety
- Ultralow design can lift low chassis sports car
- Universal joint Steering mechanism for more durability
- Double oil line hydraulic pump for fast lifting
  - Meet ASME PALD-2009
- Pedal design for easy operation and save effort.
- Patent design dual handles for easy moving Service Jack

Nature of this product is subject to wear and tear upon usage.  
Not covered under Lifetime Warranty.



### Low Profile Aluminum Service Jack 1.5 Ton

Cat. No.	Maximum Load			G.W.
97821	1.5 T	0	1	37.7 kg

- Ensure nominal deadweight achieve marked value to ensure the use safety
- Each one have been through 1.5 times tonnage overload test and passed the test before leaving the factory to ensure sufficient loading safety factor
- The valve will automatically open and unload automatically when loading weight reach to 1.1 times tonnage setting to ensure safety
- Ultralow design can lift low chassis sports car
- Universal joint Steering mechanism for more durability
- Double oil line hydraulic pump for fast lifting
  - Meet ASME PALD-2009
- Pedal design for easy operation and save effort. Patent design dual handles for easy moving Service Jack
- Made of Aluminum alloy for light weight and rust resistance

Nature of this product is subject to wear and tear upon usage.  
Not covered under Lifetime Warranty.



### Rotating Handle Hydraulic Floor Jack

Cat. No.	Maximum Load			G.W.
97881	2 T	0	1	11.2 kg
97882	3 T	0	1	17.9 kg

- High carbon steel chassis provides maximum strength in a lightweight floor jack design
- Spring loaded "T" handle on floor jack can be activated to lower load in any handle position by pulling and rotating it clockwise 1/4 turn
- Additional foot pedal pumping provides fast saddle raising to the load
- Safety by-pass and overload systems protect hydraulic block
- Chromed ram and dust seals on floor jack prevent hydraulic contamination
- Designed for use in heavy duty truck, heavy construction and agricultural equipment maintenance garages

Nature of this product is subject to wear and tear upon usage.  
Not covered under Lifetime Warranty.



### Hydraulic Bottle Jack

Cat. No.	Maximum Load			G.W.
97801	2 T	1	8	18.3 kg
97802	4 T	0	6	21.1 kg
97803	6 T	0	6	27 kg
97804	8 T	0	4	20.1 kg
97805	10 T	0	4	22.7 kg
97807	16 T	0	2	16.4 kg
97808	20 T	2	2	22.6 kg
97809	32 T	1	1	20.8 kg
97810	50 T	1	1	30.8 kg

- All steel construction
- Designed for use in automotive, industrial, construction or agricultural jobs for lifting, pushing, bending and straightening
- Adjustable top screw
- Fewer working parts, extremely smooth bearing surfaces, and close tolerances ensure trouble-free service and long life
- Screw adjustable pad Jacks can be used in vertical and horizontal positions

Nature of this product is subject to wear and tear upon usage.  
Not covered under Lifetime Warranty.



### Long Ram Jack-Portable Hydraulic Equipment

Cat. No.	Maximum Load			G.W.
97899	4 T	1	1	19 kg



- They include pump, ram, and connecting hose with quick couple for fast easy detachment.
- Easy to maintain, easy to clean remote control jacks deliver power where you need it, especially in hard to reach places on automotive frames and bodies

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### 11 Pc. Driver's Tool Set

Cat. No.			G.W.
06011	0	4	11.2 kg

**CONTENTS:**

- 1 - 1/2" Dr. L Type Extendable Socket Wrench
- 2 - 1/2" Dr. Double-end Sockets 17x19, 21x23 mm
- 1 - Linesman Pliers 7"
- 1 - Long Nose Pliers 6"
- 1 - Adjustable Wrench 8"
- 1 - Acetate Screwdriver Slotted 6x100 mm
- 1 - Acetate Screwdriver Phillips #2x100 mm
- 1 - Tape Measure 3mx16 mm
- 1 - Utility Knife 18x100 mm
- 1 - LED Flashlight



### 15 Pc. Basic Tool Set

Cat. No.			G.W.
06008	0	4	13.1 kg

**CONTENTS:**

- 3 - Acetate Screwdrivers  
Slotted 5x100mm Phillips #1x100mm  
Circuit Tester 145mm
- 12 - Accessories  
Adjustable Wrench 8"  
Long Nose Pliers 6"  
Linesman Pliers 6"  
Insulated Tape  
Fine Point Tweezer  
Tape Measure 3mx16mm  
Utility Knife  
Scissors  
Aluminum Flashlight 5#  
Mini Hacksaw  
Hickory Claw Hammer 8 oz  
Plastic Box



### 16 Pc. Motorcycle Tool Set

Cat. No.			G.W.
09512	0	4	13.3 kg

**CONTENTS:**

- 9 - Combination Wrenches 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
- 3 - Double Box End Wrenches 8x10, 14x17, 19x21 mm
- 4 - Acetate Screwdrivers  
Phillips #2x38 mm, #2x150 mm  
Slotted 6x38 mm, 6x150 mm



### 8" High Leverage Riveter

Cat. No.	Overall Height	Overall Length	Overall Width			G.W.
90501	2.8 cm	21.0 cm	9.5 cm	1	10	6 kg



- High leverage for effortless setting of rivets
- Spring loaded handle ejects rivet stem automatically
- All steel construction for durability
- Comfortable rubber handle
- Nosepieces included on the handle
- To suit rivet sizes: 2.4mm (3/32"), 3.2mm (1/8"), 4.0mm (5/32"), 4.8mm (3/16")

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### 11" High Leverage Riveter With Collection Bottle

Cat. No.	Overall Height	Overall Length	Overall Width			G.W.
90504	3.0 cm	27.5 cm	11.5 cm	10	20	16 kg



- Heavy duty steel construction
- Pulls and sets rivets up to 6.4mm
- High leverage two handle design provides the power to pull larger rivets
- Easily sets larger diameter rivets
- Plastic collection bottle attached to the tool

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### 13" High Leverage Riveter With Collection Bottle

Cat. No.	Overall Height	Overall Length	Overall Width			G.W.
90502	4.0 cm	32.2 cm	14.0 cm	1	8	10 kg



- Heavy duty steel construction
- Pulls and sets rivets up to 6.4mm
- High leverage two handle design provides the power to pull larger rivets
- Easily sets larger diameter rivets
- Plastic collection bottle attached to the tool

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

### 5 Pc. 8" File Set

Cat. No.			G.W.
03901ME	6	12	12 kg

**CONTENTS:**

- 1- Flat File, Second Cut
- 1- Half Round File, Second Cut
- 1- Square File, Second Cut
- 1- Round File, Second Cut
- 1- Three Square File, Second Cut



- Precision engineered to provide maximum gram removal per stroke and amazing longevity
- Cushion handle provides optimal balance of strength, comfort and performance
- Raised ribs, wide middle, and flared neck prevent slipping
- Hang hole for easy storage

**⚠** Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.