

Socket & Drive Tool



Socket & Drive Tool



SATA tools are designed to cater for various industries usage from automotive repair workshop to plant maintenance and repair.



SATA tools offer wide range of items for your selection from individual open stock to comprehensive advanced set items. SATA tools are your ideal choice.



Each piece of SATA tool offers exceptional value to you with highest product quality standard at a very affordable price point.

blow mold cases

SATA's blow mold cases are made of high quality P.E. materials that are very durable, secure, portable and sturdy. Compared with the traditional metalcasing, SATA's blow mold case is lighter and is much safer since there are no sharp edges and is rustproof.

Socket & Drive Tool-Set



25 Pc. 1/4" Drive 6 Point Metric Socket Set

| Cat. No. | 0 | 12 | G.W. |
|----------|---|----|---------|
| 09001 | | | 16.9 kg |

CONTENTS:

- 14 - 6pt. Metric Sockets
 - 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
- 5 - 6pt. Metric Deep Sockets 8, 10, 11, 12, 13 mm
- 6 - Accessories
 - Quick-Release Ratchet
 - Spinner Handle
 - Wobble Extensions 2", 4"
 - T-handle
 - Universal Joint



38 Pc. 1/4" Drive 6 Point Metric Socket Set

| Cat. No. | 0 | 12 | G.W. |
|----------|---|----|---------|
| 09002 | | | 16.7 kg |

CONTENTS:

- 14 - 6pt. Metric Sockets
 - 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
- 18 - Bit Sockets
 - Slotted 4, 5.5, 6.5mm Phillips #1, #2 Pozidriv #1, #2
 - Torx® T10, T15, T20, T25, T30, T40 Hex 3, 4, 5, 6, 8 mm
- 6 - Accessories
 - Quick-Release Ratchet
 - Spinner Handle
 - T-handle
 - Universal Joint
 - Wobble Extensions 2", 4"



25 Pc. 1/4" Drive 6 Point SAE Socket Set

| Cat. No. | 0 | 6 | G.W. |
|----------|---|---|------|
| 09098 | | | 9 kg |

CONTENTS:

- 10 - 6pt. S.A.E. Sockets
 - 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
- 10 - 6pt. S.A.E. Deep Sockets
 - 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
- 5 - Accessories
 - Quick-Release Ratchet
 - Spinner Handle
 - Wobble Extensions 2", 6"
 - Universal Joint



25 Pc. 1/4" Drive 12 Point Metric Socket Set

| Cat. No. | 12 | 24 | G.W. |
|----------|----|----|---------|
| 09206 | | | 13.6 kg |

CONTENTS:

- 10 - 12pt. Metric Sockets
 - 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
- 12 - Bits
 - Phillips #1, #2, #3 Slotted 5/32, 7/32, 9/32"
 - Hex 1/8, 5/32, 3/16" Torx® T15, T20, T25
- 3 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 2"
 - Bit Adapter



13 Pc. 1/4" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|----|---------|
| 09521 | 6 | 36 | 16.6 kg |

CONTENTS:

- 11 - 6pt. Metric Sockets
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
- 2 - Accessories
Quick-Release Ratchet
Wobble Extension 2"



5 Pc. 3/8" Drive Spark Plug Socket Set

| Cat. No. | | | G.W. |
|----------|---|----|-------|
| 09003 | 5 | 10 | 13 kg |

CONTENTS:

- 1 - Wobble Extension 6"
- 1 - Locking Extension 6"
- 1 - Offset Flex Head Ratchet Handle
- 2 - Spark Plug Sockets 16, 21 mm



15 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|-------|
| 08005ME | 1 | 6 | 14 kg |

CONTENTS:

- 14 - 6pt. Metric Sockets
8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 21, 22, 24, 27mm
- 1 - Quick-Release Ratchet



14 Pc. 3/8" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|----|---------|
| 09523 | 4 | 16 | 15.6 kg |

CONTENTS:

- 12 - 6pt. Metric Sockets
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
- 2 - Accessories
Quick-Release Ratchet
Wobble Extension 3"



58 Pc. 3/8" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09004 | 0 | 3 | 13.6 kg |

CONTENTS:

- 18 - 6pt. Metric Sockets
6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24 mm
- 9 - 6pt. Metric Deep Sockets 8, 10, 11, 12, 13, 14, 15, 17, 19 mm
- 2 - Spark Plug Sockets 16, 21 mm
- 24 - Bit Sockets
Slotted 5.5, 6.5, 8 mm Phillips #1, #2, #3 Pozidriv #1, #2
Torx® T10, T15, T20, T25, T30, T40, T45, T50, T55
Hex 3, 4, 5, 6, 7, 8, 10 mm
- 5 - Accessories
Quick-Release Ratchet
Wobble Extensions 3", 10"
Universal Joint
1/2" F x 3/8" M 3-Way Adapter



16 Pc. 3/8" Drive 6 Point SAE Socket Set

| Cat. No. | | | G.W. |
|----------|---|----|---------|
| 09085 | 6 | 12 | 25.6 kg |

CONTENTS:

- 11 - 6pt. S.A.E. Sockets
1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
- 5 - Accessories
Quick-Release Ratchet
Wobble Extensions 3", 6"
Flex Handle 8"
1/2" F x 3/8" M 3-Way Adapter



9 Pc. 3/8" Drive 6 Point Metric Motorcycle Tool Set

| Cat. No. | | | G.W. |
|----------|---|---|--------|
| 09511 | 0 | 6 | 8.5 kg |

CONTENTS:

- 7 - 6pt. Metric Deep Sockets 8, 9, 10, 11, 12, 13, 14 mm
- 2 - Accessories
T-handle
Wobble Extension 10"



20 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09005 | 0 | 6 | 20.9 kg |

CONTENTS:

- 12 - 6pt. Metric Sockets
10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24 mm
- 3 - 6pt. Metric Deep Sockets 13, 17, 19 mm
- 1 - Spark Plug Socket 16 mm
- 4 - Accessories
Quick-Release Ratchet
Wobble Extension 10"
Universal Joint
3/8" F x 1/2" M 3-Way Adapter



Socket & Drive Tool-Set

46 Pc. 1/2" Drive 6 Point Metric/SAE Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09006 | 0 | 3 | 21.4 kg |

CONTENTS:

20 - 6pt. Metric Sockets
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm
7 - 6pt. Metric Deep Sockets 10, 12, 13, 14, 15, 17, 19 mm
2 - Spark Plug Sockets 16, 21 mm
11 - 6pt. S.A.E. Sockets
3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1"
6 - Accessories
Quick-Release Ratchet
Flex Handle 10"
Wobble Extensions 5", 10"
Universal Joint
3/8" F x 1/2" M 3-Way Adapter



58 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09007 | 0 | 3 | 18.2 kg |

CONTENTS:

17 - 6pt. Metric Sockets
10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32 mm
8 - 6pt. Metric Deep Sockets 10, 11, 12, 13, 14, 15, 17, 19 mm
2 - Spark Plug Sockets 16, 21 mm
25 - 5/16" Shank 30L Bits
Slotted 8, 10, 12 mm Phillips #1, #2, #3, #4 Pozidriv #1, #2, #3, #4
Torx® T20, T25, T30, T40, T45, T50, T55
Hex 4, 5, 6, 8, 10, 12, 14 mm
6 - Accessories
Quick-Release Ratchet
5/16" Shank x 1/2" Dr. Bit Adapter
Wobble Extensions 5", 10"
Universal Joint
3/8" F x 1/2" M 3-Way Adapter



27 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|-------|
| 09135 | 0 | 4 | 23 kg |

CONTENTS:

20 - 6pt. Metric Sockets
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm
7 - Accessories
Quick-Release Ratchet
Wobble Extensions 5" 10"
Flex Handle 17"
Universal Joint
Spark Plug Socket
T-handle



24 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09060 | 0 | 4 | 18.8 kg |

CONTENTS:

19 - 12pt. Metric Sockets
9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm
5 - Accessories
Quick-Release Ratchet
Wobble Extensions 5", 10"
Universal Joint
T-handle



24 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09060-6 | 0 | 4 | 18.8 kg |

CONTENTS:

19 - 6pt. Metric Sockets
9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm
5 - Accessories
Quick-Release Ratchet
Wobble Extensions 5", 10"
Universal Joint
T-handle



25 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09092ME | 0 | 2 | 11.3 kg |

CONTENTS:

20 - 6pt. Metric Sockets
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32mm
1 - Spark Plug Socket 21mm
4 - Accessories
Quick-Release Ratchet
Wobble Extension 10"
Flex Handle 15"
Universal Joint



25 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|------------|---|---|---------|
| 09092ME-12 | 0 | 2 | 11.3 kg |

CONTENTS:

20 - 12pt. Metric Sockets
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32mm
1 - Spark Plug Socket 21mm
4 - Accessories
Quick-Release Ratchet
Wobble Extension 10"
Flex Handle 15"
Universal Joint



17 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09086 | 0 | 6 | 18.2 kg |

CONTENTS:

13 - 12pt. Metric Sockets
10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24 mm
1 - Spark Plug Socket 16 mm
3 - Accessories
Quick-Release Ratchet
Wobble Extension 5"
Flex Handle 10"



Socket & Drive Tool-Set

20 Pc. 1/2" Drive 6 and 12 Point SAE Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09087 | 0 | 4 | 18.7 kg |

CONTENTS:
 8 - 6pt. S.A.E. Sockets 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4"
 7 - 12pt. S.A.E. Sockets 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, 1-1/4"
 5 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 Flex Handle 15"
 3/8" F x 1/2" M 3-Way Adapter



22 Pc. 1/2" Drive 12 Point SAE Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09088 | 0 | 4 | 22.9 kg |

CONTENTS:
 15 - 12pt. S.A.E. Sockets
 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, 1-1/4"
 7 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 Flex Handle 10"
 T-handle
 Universal Joint
 Speed Handle



28 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09090 | 0 | 4 | 24.9 kg |

CONTENTS:
 21 - 12pt. Metric Sockets
 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30, 32 mm
 7 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 Flex Handle 10"
 T-handle
 Universal Joint
 Speed Handle



28 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09090-6 | 0 | 4 | 20.5 kg |

CONTENTS:
 21 - 6pt. Metric Sockets
 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30, 32mm
 7 - Accessories
 Quick-Release Ratchet
 Wobble Extension Bars 5", 10"
 Flex Handle 10"
 Sliding T-Bar
 Universal Joint
 Speed Handle



NEW

Socket & Drive Tool-Set

18 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09203 | 0 | 6 | 21.5 kg |

CONTENTS:
 14 - 12pt. Metric Sockets
 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 24, 27, 30, 32 mm
 4 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 T-handle



18 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09204 | 0 | 6 | 21.5 kg |

CONTENTS:
 14 - 12pt. Metric Sockets
 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 24, 27, 30, 32 mm
 4 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 T-handle



24 Pc. 1/2" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09205 | 0 | 4 | 21.7 kg |

CONTENTS:
 18 - 12pt. Metric Sockets
 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 26, 27, 28, 30, 32 mm
 6 - Accessories
 Quick-Release Ratchet
 Wobble Extensions 5", 10"
 T-handle
 Universal Joint
 Speed Handle



13 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09525 | 2 | 8 | 13.9 kg |

CONTENTS:
 11 - 6pt. Metric Sockets
 10, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24 mm
 2 - Accessories
 Quick-Release Ratchet
 Wobble Extension 5"



Socket & Drive Tool-Set

26 Pc. 1/2" Drive 6 Point Metric Socket Tool Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09501 | 0 | 4 | 19.8 kg |

CONTENTS:

- 12 - 6pt. Metric Sockets
 - 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24 mm
- 3 - 6pt. Metric Deep Sockets 13, 17, 19 mm
- 1 - Spark Plug Socket 16 mm
- 4 - Acetate Screwdrivers
 - Slotted 6x38mm, 5x75 mm Phillips #2x38 mm, #2x100 mm
- 6 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 10"
 - Universal Joint
 - 3/8" F x 1/2" M 3-Way Adapter
 - Long Nose Pliers 6"
 - Linesman's Pliers 8"



26 Pc. 1/2" Drive 6 Point Metric Socket Tool Set

| Cat. No. | | | G.W. |
|----------|---|---|--------|
| 09502 | 0 | 2 | 112 kg |

CONTENTS:

- 9 - 6pt. Metric Sockets 10, 12, 14, 16, 17, 19, 21, 22, 24 mm
- 4 - Acetate Screwdrivers
 - Slotted 6x100mm, 6x150 mm Phillips #2x100 mm, #2x150 mm
- 13 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 5"
 - Flex Handle 15"
 - Combination Wrenches 8, 10, 12, 14, 16, 17, 19mm
 - Long Nose Pliers 6"
 - Diagonal Pliers 6"
 - Linesman's Pliers 7"



26 Pc. 1/2" Drive 6 Point Metric Socket Tool Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09504 | 0 | 2 | 14.8 kg |

CONTENTS:

- 9 - 6pt. Metric Sockets 10, 12, 13, 14, 17, 19, 21, 22, 24 mm
- 4 - Acetate Screwdrivers
 - Slotted 5x75mm, 6x150 mm Phillips #1x75 mm, #2x150 mm
- 13 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 5"
 - Flex Handle 15"
 - Combination Wrenches 8, 10, 12, 14, 16, 17, 19 mm
 - Long Nose Pliers 6"
 - Diagonal Pliers 6"
 - Linesman's Pliers 7"



25 Pc. 1/2" Drive 6 and 12 Point Metric Socket Wrench Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09506 | 0 | 6 | 16.5 kg |

CONTENTS:

- 12 - 12pt. Metric Sockets
 - 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24 mm
- 3 - 6pt. Metric Deep Sockets 13, 17, 19 mm
- 1 - Spark Plug Socket 16 mm
- 9 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 10"
 - Universal Joint
 - 3/8" F x 1/2" M 3-Way Adapter
 - Combination Wrenches 10, 11, 12, 13, 14mm



25 Pc. 1/2" Drive 6 Point Metric Socket Wrench Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09506-6 | 0 | 6 | 20.6 kg |

CONTENTS:

- 12 - 6pt. Metric Sockets
 - 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24mm
- 3 - 6pt. Metric Deep Sockets 13, 17, 19mm
- 1 - Spark Plug Socket 16mm
- 9 - Accessories
 - Quick-Release Ratchet
 - Wobble Extension 10"
 - Universal Joint
 - 3/8" F x 1/2" M 3-Way Adapter
 - Combination Wrenches 10, 11, 12, 13, 14mm



12 Pc. 1/2" Drive Bit Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09055 | 0 | 5 | 10.8 kg |

CONTENTS:

- 2 - 50L Hex Bit Sockets 12, 17mm
- 1 - 70L Hex Bit Socket 6mm
- 1 - 100L Hex Bit Socket 7mm
- 1 - 120L Hex Bit Socket 8mm
- 2 - 140L Hex Bit Sockets 6, 10mm
- 1 - 180L Hex Bit Socket 5mm
- 1 - 250L Hex Bit Socket 6mm
- 1 - 100L Triple Square Bit Socket M8
- 1 - 120L Triple Square Bit Socket M10
- 1 - 140L Triple Square Bit Socket M12



Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

Socket & Drive Tool-Set

35 Pc. 1/4" and 3/8" Drive E-torx Socket and Wrench Set

| Cat. No. | | | G.W. |
|----------|---|----|---------|
| 09010 | 0 | 12 | 18.7 kg |

CONTENTS:

- 7 - 1/4" Shank Tamper-Proof Torx® Bits
 - T10, T15, T20, T25, T27, T30, T40
- 12 - 3/8" Dr. E-Torx® Sockets
 - E4, E5, E6, E7, E8, E10, E11, E12, E14, E16, E18, E20
- 11 - 3/8" Dr. Torx® Bit Sockets
 - T10, T15, T20, T25, T27, T30, T40, T45, T50, T55, T60
- 5 - Accessories
 - E-Torx® Wrenches E6xE8, E10xE12, E14xE18, E20xE24
 - 1/4" Shank x 3/8" Dr. Bit Adapter



18 Pc. 1/4" and 1/2" Drive Bit Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09051 | 0 | 5 | 10.5 kg |

CONTENTS:

- 6 - 1/4" Dr. Bit Sockets
 - Slotted 4, 5.5, 6.5 mm Phillips #1, #2, #3
- 6 - 1/2" Dr. 50L Triple Square Bit Sockets
 - M5, M6, M8, M10, M12, M14
- 6 - 1/2" Dr. 100L Triple Square Bit Sockets
 - M5, M6, M8, M10, M12, M14



Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

Socket & Drive Tool-Set

18 Pc. 1/4" and 1/2" Drive Torx® Bit Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|--------|
| 09052 | 0 | 5 | 9.3 kg |

CONTENTS:

6 - 1/4"Dr. Torx® Bit Sockets T10, T15, T20, T25, T30, T40
 6 - 1/2"Dr. 50L Torx® Bit Sockets T30, T40, T45, T50, T55, T60
 6 - 1/2"Dr. 100L Torx® Bit Sockets T30, T40, T45, T50, T55, T60



Nature of this product is subject to wear and tear upon usage.
 Not covered under Lifetime Warranty.

18 Pc. 1/4" and 1/2" Drive Metric Hex Bit Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|--------|
| 09053 | 0 | 5 | 9.3 kg |

CONTENTS:

6 - 1/4"Dr. Hex Bit Sockets 3, 4, 5, 6, 7, 8mm
 6 - 1/2"Dr. 50L Hex Bit Sockets 5, 6, 7, 8, 10, 12mm
 6 - 1/2"Dr. 100L Hex Bit Sockets 5, 6, 7, 8, 10, 12mm



Nature of this product is subject to wear and tear upon usage.
 Not covered under Lifetime Warranty.

65 Pc. 1/4" and 3/8" Drive 6 Point Metric/SAE Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09011 | 0 | 3 | 10.1 kg |

CONTENTS:

12 - 1/4"Dr. 6pt. Metric Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 mm
 10 - 1/4"Dr. 6pt. S.A.E. Sockets 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
 18 - 1/4" Shank 25L Bits
 Slotted 4, 5.5, 6.5 mm
 Phillips #1, #2, #3
 Torx® T10, T15, T20, T25, T30, T40
 Hex 3, 4, 5, 6, 7, 8 mm
 10 - 3/8"Dr. 6pt. Metric Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
 8 - 3/8"Dr. 6pt. S.A.E. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16"
 1 - 3/8"Dr. Spark Plug Socket 16 mm
 6 - Accessories
 3/8"Dr. Quick-Release Ratchet
 3/8"Dr. Wobble Extension 3"
 3/8"Dr. Universal Joint
 1/4" Shank x 1/4"Dr. Bit Adapter
 3/8" x 1/4" Adapter
 1/4"Dr. Spinner Handle



Socket & Drive Tool-Set

86 Pc. 1/4" and 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09013 | 0 | 3 | 19.6 kg |

CONTENTS:

14 - 1/4"Dr. 6pt. Metric Sockets 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
 8 - 1/4"Dr. 6pt. Metric Deep Sockets 6, 7, 8, 9, 10, 11, 12, 13 mm
 17 - 1/4"Dr. Bit Sockets
 Slotted 4, 5.5, 6.5 mm
 Phillips #1, #2
 Pozidriv #1, #2
 Torx® T8, T10, T15, T20, T25, T30
 Hex 3, 4, 5, 6 mm
 2 - 1/2"Dr. Spark Plug Sockets 16, 21 mm
 14 - 1/2"Dr. 6pt. Metric Sockets
 10, 13, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32 mm
 4 - 1/2"Dr. 6pt. Metric Deep Sockets 14, 15, 17, 19 mm
 15 - 5/16" Shank 30L Bits
 Slotted 8, 10, 12mm
 Phillips #3, #4
 Pozidriv #3, #4
 Torx® T40, T45, T50, T55
 Hex 8, 10, 12, 14 mm
 12 - Accessories
 1/4", 1/2"Dr. Quick-Release Ratchets
 1/4"Dr. T-handle
 1/4"Dr. Wobble Extensions 2", 4"
 1/2"Dr. Wobble Extensions 5", 10"
 1/4", 1/2"Dr. Universal Joints
 3/8" x 1/2" M 3-Way Adapter
 1/4"Dr. Spinner Handle
 5/16" Shank x 1/2"Dr. Bit Adapter



76 Pc. 1/4" and 1/2" Drive 6 Point Metric Socket Wrench Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09519 | 0 | 3 | 20.6 kg |

CONTENTS:

7 - 1/4"Dr. 6pt. Metric Sockets 8, 9, 10, 11, 12, 13, 14 mm
 18 - 1/4"Dr. Bit Sockets
 Slotted 4, 5.5, 6.5 mm
 Phillips #1, #2
 Pozidriv #1, #2
 Torx® T8, T10, T15, T20, T25, T30, T40
 Hex 3, 4, 5, 6 mm
 12 - 1/2"Dr. 6pt. Metric Sockets 8, 10, 12, 13, 14, 17, 19, 22, 24, 27, 30, 32 mm
 15 - 5/16" Shank 30L Bits
 Slotted 8, 10, 12 mm
 Phillips #3, #4
 Pozidriv #3, #4
 Torx® T40, T45, T50, T55
 Hex 8, 10, 12, 14 mm
 2 - 1/2"Dr. Spark Plug Sockets 16, 21 mm
 22 - Accessories
 1/4", 1/2"Dr. Quick-Release Ratchets
 1/4"Dr. T-handle
 1/4"Dr. Flex Extension
 1/4"Dr. Wobble Extensions 2", 4"
 1/2"Dr. Wobble Extensions 5", 10"
 1/4", 1/2"Dr. Universal Joints
 1/4"Dr. Spinner Handle
 1/2"Dr. T-handle
 5/16" Shank x 1/2"Dr. Bit Adapter
 Combination Wrenches 8, 10, 11, 12, 13, 14, 17, 19, 22 mm



Socket & Drive Tool-Set

120 Pc. 1/4", 3/8" and 1/2" Drive 6 Point Metric/SAE Socket Wrench Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09014 | 0 | 2 | 18.9 kg |

CONTENTS:

10 - 1/4" Dr. 6pt. Metric Sockets 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
 10 - 1/4" Dr. 6pt. S.A.E. Sockets 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
 4 - 1/4" Dr. 6pt. Metric Deep Sockets 8, 9, 10, 12 mm
 7 - 1/4" Shank 25L Tamper-Proof Torx® Bits T10, T15, T20, T25, T27, T30, T40
 11 - 3/8" Dr. 6pt. Metric Sockets 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
 9 - 3/8" Dr. 6pt. S.A.E. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
 4 - 3/8" Dr. 6pt. Metric Deep Sockets 13, 14, 15, 17 mm
 2 - 3/8" Dr. Spark Plug Sockets 16, 21 mm
 17 - 3/8" Dr. Bit Sockets
 Slotted 5.5, 6.5mm Phillips #1, #2 Pozidriv #1, #2 Torx® T20, T30, T40
 Tamper-Proof Torx® T45, T50, T55, T60 Hex 3, 4, 5, 6 mm
 8 - 3/8" Dr. E-Torx® Sockets E8, E10, E11, E12, E14, E16, E18, E20
 7 - 1/2" Dr. 6pt. Metric Sockets 20, 21, 22, 24, 27, 30, 32 mm
 4 - 1/2" Dr. 6pt. S.A.E. Sockets 5/16, 1, 1-1/16, 1-1/4"
 4 - 1/2" Dr. 6pt. Metric Impact Sockets 17, 19, 21, 23mm
 23 - Accessories
 1/4", 3/8", 1/2" Dr. Quick-Release Ratchets
 1/4" Dr. Spinner Handle
 1/4" Dr. Wobble Extension 2"
 3/8" Dr. Wobble Extensions 3", 6"
 1/2" Dr. Wobble Extensions 5", 10"
 1/4", 3/8", 1/2" Dr. Universal Joints
 1/4" Shank x 1/4" Dr. Bit Adapter
 Combination Wrenches 8, 9, 10, 11, 12, 13, 14, 17, 18, 19 mm



150 Pc. 1/4", 3/8" and 1/2" Drive 6 and 12 Point Metric/SAE Socket Wrench Set

| Cat. No. | | | G.W. |
|----------|---|---|-------|
| 09510 | 0 | 1 | 14 kg |

CONTENTS:

10 - 1/4" Dr. 6pt. Metric Sockets 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
 10 - 1/4" Dr. 6pt. S.A.E. Sockets 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
 6 - 1/4" Dr. 6pt. Metric Deep Sockets 4, 5, 6, 7, 8, 9 mm
 11 - 3/8" Dr. 6pt. Metric Sockets 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
 9 - 3/8" Dr. 6pt. S.A.E. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
 6 - 3/8" Dr. 6pt. Metric Deep Sockets 10, 11, 12, 13, 14, 15 mm
 2 - 3/8" Dr. Spark Plug Sockets 16, 21 mm
 22 - 3/8" Dr. Bit Sockets
 Slotted 4, 5.5, 6.5 mm Phillips #1, #2, #3 Pozidriv #1, #2, #3
 Torx® T20, T30, T40 Tamper-Proof T45, T50, T55, T60 Hex 3, 4, 5, 6, 8, 10 mm
 8 - 3/8" Dr. 6pt. E-Torx® Sockets E8, E10, E11, E12, E14, E16, E18, E20
 4 - 1/2" Dr. 6pt. Metric Impact Sockets 17, 19, 21, 23 mm
 7 - 1/2" Dr. 12pt. Metric Sockets 20, 21, 22, 24, 27, 30, 32 mm
 4 - 1/2" Dr. 12pt. S.A.E. Sockets 15/16, 1, 1-1/16, 1-1/4"
 6 - 1/2" Dr. 6pt. Metric Deep Sockets 10, 12, 13, 14, 17, 19 mm
 45 - Accessories
 1/4", 3/8", 1/2" Dr. Quick-Release Ratchets
 1/4" Dr. Bit Adapter
 1/4" Dr. Spinner Handle
 1/4" Dr. Wobble Extension 4"
 3/8" Dr. Locking Extensions 3", 6"
 1/2" Dr. Wobble Extension 5"
 1/2" Dr. Locking Extension 10"
 1/4", 3/8", 1/2" Dr. Universal Joints
 1/4" Shank Torx® Bits (Tamper-Proof) T10, T15, T20, T25, T27, T30, T40
 Hex Key Metric Set (10pcs)
 Combination Wrenches 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
 Double Box Ratcheting Wrenches 8x10, 12x13, 17x19 mm



Socket & Drive Tool-Set

15 Pc. 3/4" Drive 12 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|---------|
| 09015 | 0 | 1 | 15.4 kg |

CONTENTS:

10 - 12pt. Metric Sockets 30, 32, 34, 36, 38, 41, 46, 50, 55, 60 mm
 5 - Accessories
 Quick-Release Ratchet
 T-handle
 Extensions 4", 8"
 Universal Joint



16 Pc. 1/2" Drive 6 Point Metric Socket Set

| Cat. No. | | | G.W. |
|----------|---|---|-------|
| 09520 | 1 | 8 | 14 kg |

CONTENTS:

10 - 6pt. Metric Sockets
 8, 10, 12, 13, 14, 17, 19, 21, 22, 24
 6 - 6pt. Metric Deep Sockets
 10, 12, 14, 17, 19, 21



3 Pc. L-Shaped Wheel Wrench Set

| Cat. No. | | | G.W. |
|----------|----|----|---------|
| 09531 | 10 | 10 | 12.3 kg |

CONTENTS:


13920 - 1/2" Dr. Offset Handle 345mm
 13921 - 1/2" Dr. Dual Head Socket 17x19mm
 13922 - 1/2" Dr. Dual Head Socket 21x23mm



1/4" Drive 6 Point SAE Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|-----|--------|
| 11101 | 5/32 in | 11.8 mm | 6.9 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11102 | 3/16 in | 11.8 mm | 7.8 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11103 | 7/32 in | 11.8 mm | 8.5 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11104 | 1/4 in | 11.8 mm | 9.5 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11105 | 9/32 in | 11.8 mm | 10.7 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11106 | 5/16 in | 11.8 mm | 11.8 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11107 | 11/32 in | 12.5 mm | 12.5 mm | 24.5 mm | 12 | 168 | 5 kg |
| 11108 | 3/8 in | 13.8 mm | 13.8 mm | 24.5 mm | 12 | 168 | 5.1 kg |
| 11109 | 7/16 in | 15.7 mm | 15.7 mm | 24.5 mm | 6 | 84 | 3 kg |
| 11110 | 1/2 in | 17.3 mm | 17.3 mm | 24.5 mm | 6 | 84 | 3.4 kg |

ANSI B107.1




- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive 6 Point SAE Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|-----|---------|
| 11201 | 3/16 in | 11.9 mm | 7.85 mm | 49 mm | 12 | 396 | 10.9 kg |
| 11202 | 7/32 in | 11.9 mm | 8.85 mm | 49 mm | 12 | 396 | 11.4 kg |
| 11203 | 1/4 in | 11.9 mm | 9.9 mm | 49 mm | 12 | 396 | 12.5 kg |
| 11204 | 9/32 in | 11.9 mm | 10.95 mm | 49 mm | 12 | 396 | 12 kg |
| 11205 | 5/16 in | 11.9 mm | 11.9 mm | 49 mm | 12 | 396 | 11.4 kg |
| 11206 | 11/32 in | 13.1 mm | 13.1 mm | 49 mm | 6 | 84 | 3.6 kg |
| 11207 | 3/8 in | 14.6 mm | 14.6 mm | 49 mm | 6 | 84 | 4.6 kg |
| 11208 | 7/16 in | 15.9 mm | 15.9 mm | 49 mm | 6 | 84 | 5.7 kg |
| 11209 | 1/2 in | 17.9 mm | 17.9 mm | 49 mm | 6 | 72 | 5.3 kg |

ANSI B107.1




- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive 6 Point Metric Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|-----|--------|
| 11301 | 3.5 mm | 11.8 mm | 6.1 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11302 | 4 mm | 11.8 mm | 6.7 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11303 | 4.5 mm | 11.8 mm | 7.3 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11304 | 5 mm | 11.8 mm | 8.0 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11305 | 5.5 mm | 11.8 mm | 8.6 mm | 24.5 mm | 12 | 384 | 7.1 kg |
| 11306 | 6 mm | 11.8 mm | 9.2 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11307 | 7 mm | 11.8 mm | 10.7 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11308 | 8 mm | 11.8 mm | 11.8 mm | 24.5 mm | 12 | 384 | 7.3 kg |
| 11309 | 9 mm | 13.1 mm | 13.1 mm | 24.5 mm | 12 | 168 | 4.1 kg |
| 11310 | 10 mm | 14.3 mm | 14.3 mm | 24.5 mm | 12 | 168 | 4.4 kg |
| 11311 | 11 mm | 15.8 mm | 15.8 mm | 24.5 mm | 6 | 84 | 3.1 kg |
| 11312 | 12 mm | 16.8 mm | 16.8 mm | 24.5 mm | 6 | 84 | 3.2 kg |
| 11313 | 13 mm | 17.9 mm | 17.9 mm | 24.5 mm | 6 | 84 | 3.6 kg |
| 11314 | 14 mm | 19.5 mm | 19.5 mm | 24.5 mm | 6 | 84 | 4 kg |

ANSI B107.5M
DIN 3124




- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive 6 Point Metric Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|-----|---------|
| 11401 | 4 mm | 11.9 mm | 6.7 mm | 49 mm | 12 | 396 | 10.3 kg |
| 11402 | 5 mm | 11.9 mm | 8.0 mm | 49 mm | 12 | 396 | 10.9 kg |
| 11403 | 6 mm | 11.9 mm | 9.2 mm | 49 mm | 12 | 396 | 11.4 kg |
| 11404 | 7 mm | 11.9 mm | 10.8 mm | 49 mm | 12 | 396 | 12.5 kg |
| 11405 | 8 mm | 11.9 mm | 11.9 mm | 49 mm | 12 | 396 | 12.5 kg |
| 11406 | 9 mm | 13.1 mm | 13.1 mm | 49 mm | 6 | 84 | 3.4 kg |
| 11407 | 10 mm | 14.6 mm | 14.6 mm | 49 mm | 6 | 84 | 3.3 kg |
| 11408 | 11 mm | 15.9 mm | 15.9 mm | 49 mm | 6 | 84 | 5.1 kg |
| 11409 | 12 mm | 16.9 mm | 16.9 mm | 49 mm | 6 | 84 | 5.4 kg |
| 11410 | 13 mm | 17.9 mm | 17.9 mm | 49 mm | 6 | 72 | 5 kg |

ANSI B107.5M
DIN 3124



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11905 | 143 mm | 4 | 24 | 4.2 kg |

ANSI B107.10M
DIN 3122



- Made of Chrom Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/4" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11906 | 143 mm | 4 | 24 | 4.1 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

Magnetic Pickup Tool

| Cat. No. | Overall Length Min | Overall Length Max | | | G.W. |
|----------|--------------------|--------------------|---|----|------|
| 11924 | 165 mm | 545 mm | 6 | 36 | 3 kg |



- Long shaft gets in tight places
- Powerful magnets are fitted into the brass sleeve on these units

1/4" Drive Quick-Release Round Head Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11901 | 142 mm | 4 | 24 | 4.2 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Quick-release capability to easily eject an engaged socket even under slippery conditions.

1/4" Drive Heavy Duty Offset Quick-Release Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11970 | 153 mm | 4 | 24 | 4.2 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/4" Drive Flex Handle / Breaker Bar

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11909 | 140 mm | 6 | 36 | 5.2 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
 - Direction change function
- ⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive T-handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11910 | 100 mm | 6 | 36 | 2.7 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive Universal Joint

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|----|-----|--------|
| 11912 | 1/4" | 1/4" | 34.7 mm | 12 | 168 | 6.8 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive Adapter

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|----|-----|--------|
| 11913 | 1/4" | 3/8" | 25.5 mm | 12 | 384 | 9.7 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive Bits Adapter

| Cat. No. | Size | | | G.W. |
|----------|--------|----|-----|--------|
| 11914 | 1/4 in | 12 | 384 | 9.7 kg |

ANSI B107.10M



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/4" Drive Flex Extension

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 11922 | 150 mm | 6 | 36 | 3.6 kg |



- Made of Chrome Vanadium steel

1/4" Drive Wobble Extensions

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|------|----------------|----|-----|--------|
| 11903 | 2 in | 50 mm | 12 | 396 | 12 kg |
| 11904 | 4 in | 100 mm | 12 | 72 | 4.6 kg |

ANSI B107.10M
DIN 3123




- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive 6 Point SAE Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|-----|--------|
| 12101 | 1/4 in | 17.2 mm | 10 mm | 25 mm | 6 | 192 | 5.5 kg |
| 12102 | 5/16 in | 17.2 mm | 11.7 mm | 25 mm | 6 | 192 | 5.5 kg |
| 12103 | 3/8 in | 17.2 mm | 13.8 mm | 25 mm | 6 | 192 | 5.7 kg |
| 12104 | 7/16 in | 17.2 mm | 16 mm | 25 mm | 6 | 192 | 6.3 kg |
| 12105 | 1/2 in | 17.9 mm | 17.9 mm | 25 mm | 6 | 192 | 6.8 kg |
| 12106 | 9/16 in | 19.7 mm | 19.7 mm | 25 mm | 6 | 84 | 3.2 kg |
| 12107 | 5/8 in | 22.2 mm | 22.2 mm | 25 mm | 6 | 84 | 4.5 kg |
| 12108 | 11/16 in | 23.9 mm | 23.9 mm | 25 mm | 6 | 72 | 4.7 kg |
| 12109 | 3/4 in | 25.9 mm | 25.9 mm | 25 mm | 6 | 72 | 5.4 kg |
| 12110 | 13/16 in | 27.9 mm | 27.9 mm | 28 mm | 4 | 48 | 4.8 kg |
| 12111 | 7/8 in | 29.7 mm | 29.7 mm | 28 mm | 4 | 48 | 5.1 kg |

ANSI B107.1



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive 6 Point SAE Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|-----|---------|
| 12201 | 3/8 in | 16.8 mm | 13.8 mm | 63.5 mm | 6 | 198 | 10.9 kg |
| 12202 | 7/16 in | 16.8 mm | 16 mm | 63.5 mm | 6 | 198 | 11.3 kg |
| 12203 | 1/2 in | 18.3 mm | 18.3 mm | 63.5 mm | 6 | 72 | 6.2 kg |
| 12204 | 9/16 in | 19.8 mm | 19.8 mm | 63.5 mm | 6 | 72 | 6.5 kg |
| 12205 | 5/8 in | 22 mm | 22 mm | 63.5 mm | 6 | 72 | 7.2 kg |
| 12206 | 11/16 in | 23.8 mm | 23.8 mm | 63.5 mm | 6 | 72 | 9.7 kg |
| 12207 | 3/4 in | 25.8 mm | 25.8 mm | 63.5 mm | 6 | 72 | 11.6 kg |
| 12208 | 13/16 in | 27.8 mm | 27.8 mm | 63.5 mm | 4 | 48 | 9.8 kg |
| 12209 | 7/8 in | 29.8 mm | 29.8 mm | 63.5 mm | 4 | 48 | 10.3 kg |

ANSI B107.1



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.



3/8" Drive 6 Point Metric Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|-----|--------|
| 12301 | 6 mm | 17 mm | 9.3 mm | 25 mm | 6 | 192 | 5.5 kg |
| 12302 | 7 mm | 17 mm | 10.8 mm | 25 mm | 6 | 192 | 5.7 kg |
| 12303 | 8 mm | 17 mm | 12 mm | 25 mm | 6 | 192 | 5.8 kg |
| 12304 | 9 mm | 17 mm | 12.9 mm | 25 mm | 6 | 192 | 6 kg |
| 12305 | 10 mm | 17 mm | 14.5 mm | 25 mm | 6 | 192 | 6 kg |
| 12306 | 11 mm | 17 mm | 15.8 mm | 25 mm | 6 | 192 | 6 kg |
| 12307 | 12 mm | 17 mm | 17 mm | 25 mm | 6 | 192 | 6.3 kg |
| 12308 | 13 mm | 18.3 mm | 18.3 mm | 25 mm | 6 | 84 | 3.6 kg |
| 12309 | 14 mm | 19.5 mm | 19.5 mm | 25 mm | 6 | 84 | 3.8 kg |
| 12310 | 15 mm | 20.8 mm | 20.8 mm | 25 mm | 6 | 84 | 4 kg |
| 12311 | 16 mm | 22 mm | 22 mm | 25 mm | 6 | 84 | 4.4 kg |
| 12312 | 17 mm | 23.3 mm | 23.3 mm | 25 mm | 6 | 72 | 4.3 kg |
| 12313 | 18 mm | 23.8 mm | 23.8 mm | 25 mm | 6 | 72 | 4.4 kg |
| 12314 | 19 mm | 25.5 mm | 25.5 mm | 25 mm | 6 | 72 | 4.5 kg |
| 12315 | 20 mm | 27 mm | 27 mm | 28 mm | 4 | 48 | 4 kg |
| 12316 | 21 mm | 27.9 mm | 27.9 mm | 28 mm | 4 | 48 | 4.1 kg |
| 12317 | 22 mm | 29.5 mm | 29.5 mm | 28 mm | 4 | 48 | 4.8 kg |
| 12318 | 24 mm | 31.9 mm | 31.9 mm | 28 mm | 4 | 48 | 4.9 kg |

ANSI B107.5M
DIN 3124



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive 6 Point Metric Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|-----|---------|
| 12401 | 8 mm | 16.8 mm | 12 mm | 63.5 mm | 6 | 198 | 10.9 kg |
| 12402 | 9 mm | 16.8 mm | 12.9 mm | 63.5 mm | 6 | 198 | 10.9 kg |
| 12403 | 10 mm | 16.8 mm | 14.5 mm | 63.5 mm | 6 | 198 | 10.9 kg |
| 12404 | 11 mm | 16.8 mm | 15.8 mm | 63.5 mm | 6 | 198 | 11.3 kg |
| 12405 | 12 mm | 16.8 mm | 16.8 mm | 63.5 mm | 6 | 198 | 12.5 kg |
| 12406 | 13 mm | 16.8 mm | 18.8 mm | 63.5 mm | 6 | 72 | 6.2 kg |
| 12407 | 14 mm | 19.5 mm | 19.5 mm | 63.5 mm | 6 | 72 | 6.5 kg |
| 12408 | 15 mm | 20.8 mm | 20.8 mm | 63.5 mm | 6 | 72 | 7.2 kg |
| 12409 | 16 mm | 22 mm | 22 mm | 63.5 mm | 6 | 72 | 7.3 kg |
| 12410 | 17 mm | 23.8 mm | 23.8 mm | 63.5 mm | 6 | 72 | 9.7 kg |
| 12411 | 18 mm | 23.8 mm | 23.8 mm | 63.5 mm | 6 | 72 | 9.9 kg |
| 12412 | 19 mm | 25.5 mm | 25.5 mm | 63.5 mm | 6 | 72 | 11.6 kg |
| 12413 | 20 mm | 27 mm | 27 mm | 63.5 mm | 4 | 48 | 9.1 kg |
| 12414 | 21 mm | 27.8 mm | 27.8 mm | 63.5 mm | 4 | 48 | 9.8 kg |
| 12415 | 22 mm | 29.5 mm | 29.5 mm | 63.5 mm | 4 | 48 | 10.3 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drives, pneumatic impact wrench and/or extenders.




ANSI B107.5M
DIN 3124

3/8" Drive External Torx® Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|-----|--------|
| 12701 | E4 | 17 mm | 7 mm | 26 mm | 6 | 192 | 3.9 kg |
| 12702 | E5 | 17 mm | 8 mm | 26 mm | 6 | 192 | 3.9 kg |
| 12703 | E6 | 17 mm | 8 mm | 26 mm | 6 | 192 | 3.9 kg |
| 12704 | E7 | 17 mm | 9 mm | 26 mm | 6 | 192 | 3.9 kg |
| 12705 | E8 | 17 mm | 10.5 mm | 26 mm | 6 | 192 | 4.6 kg |
| 12706 | E10 | 17 mm | 13 mm | 26 mm | 6 | 192 | 5.6 kg |
| 12707 | E11 | 17 mm | 14 mm | 26 mm | 6 | 192 | 5.6 kg |
| 12708 | E12 | 17 mm | 15 mm | 26 mm | 6 | 192 | 6.5 kg |
| 12709 | E14 | 18.3 mm | 18.3 mm | 28.5 mm | 6 | 84 | 4.7 kg |
| 12710 | E16 | 18.3 mm | 18.3 mm | 28.5 mm | 6 | 84 | 5 kg |
| 12711 | E18 | 19.5 mm | 18.5 mm | 28.5 mm | 6 | 84 | 5 kg |
| 12712 | E20 | 22 mm | 22 mm | 30.5 mm | 6 | 84 | 6.1 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.



3/8" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12971 | 200 mm | 4 | 24 | 2.7 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

3/8" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12972 | 200 mm | 4 | 24 | 2.3 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

3/8" Drive Heavy Duty Offset Quick-Release Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12970 | 217 mm | 4 | 24 | 8.3 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

3/8" Drive Quick-Release Round Head Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12901 | 197 mm | 4 | 24 | 8.3 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Quick-release capability to easily eject an engaged socket even under slippery conditions

3/8" Drive Quick-Release Stubby Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12960 | 115 mm | 6 | 36 | 6.3 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

3/8" Drive Wobble Extensions

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|-------|----------------|---|----|--------|
| 12903 | 3 in | 75 mm | 6 | 72 | 6.4 kg |
| 12904 | 6 in | 150 mm | 6 | 36 | 6.2 kg |
| 12905 | 10 in | 250 mm | 6 | 36 | 9.5 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel
- ⚠** These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Locking Extensions

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|-------|----------------|---|----|--------|
| 12906 | 3 in | 75 mm | 6 | 72 | 6.7 kg |
| 12907 | 6 in | 150 mm | 6 | 36 | 6.1 kg |
| 12908 | 10 in | 250 mm | 6 | 36 | 9.3 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive T-handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12910 | 165 mm | 6 | 36 | 6.4 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Universal Joint

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|---------|
| 12912 | 3/8" | 3/8" | 51.2 mm | 6 | 72 | 10.7 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Flex Handle / Breaker Bar

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 12909 | 140 mm | 6 | 36 | 10.6 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Direction change function

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Offset Flex Quick-Release Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 12911 | 275 mm | 4 | 24 | 10.7 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Adapters

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|-----|--------|
| 12913 | 3/8" | 1/4" | 25.6 mm | 6 | 192 | 8.4 kg |
| 12914 | 3/8" | 1/2" | 25.7 mm | 6 | 84 | 6.1 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Metric Spark Plug Sockets

| Cat. No. | Fastener Size | | | G.W. |
|----------|---------------|---|----|--------|
| 12915 | 16 mm | 6 | 72 | 8.3 kg |
| 12916 | 21 mm | 6 | 72 | 12 kg |

ANSI B107.34M



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Bits Adapter

| Cat. No. | Size | | | G.W. |
|----------|--------|---|-----|--------|
| 12917 | 1/4 in | 6 | 192 | 9.1 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive 12 Point Metric Thin Wall Spark Plug Sockets

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|--------|
| 12925 | 3/8" | 1/2" | 43.6 mm | 6 | 48 | 3.6 kg |



- Made of Chrome Vanadium Steel
- There is a rubber insert to retain spark plug

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive SAE Spark Plug Sockets

| Cat. No. | Fastener Size | | | G.W. |
|----------|---------------|---|----|--------|
| 12919 | 5/8 in | 6 | 72 | 8.3 kg |
| 12920 | 13/16 in | 6 | 72 | 12 kg |

ANSI B107.34M



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Drive Flex Extension

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|--------|
| 12922 | 200 mm | 6 | 36 | 5.8 kg |



- Made of Chrome Vanadium steel

3/8" Drive 3-Way Adapter

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|--------|
| 12930 | 3/8" | 1/2" | 43.6 mm | 6 | 72 | 8.1 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel


⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive 6 Point SAE Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13101 | 5/16 in | 22.2 mm | 12.5 mm | 37.8 mm | 4 | 84 | 4.9 kg |
| 13102 | 3/8 in | 22.2 mm | 14.5 mm | 37.8 mm | 6 | 84 | 4.9 kg |
| 13103 | 7/16 in | 22.2 mm | 17 mm | 37.8 mm | 6 | 84 | 5.2 kg |
| 13104 | 1/2 in | 22.2 mm | 18.6 mm | 37.8 mm | 6 | 84 | 5.2 kg |
| 13105 | 9/16 in | 22.2 mm | 20.6 mm | 37.8 mm | 6 | 84 | 5.4 kg |
| 13106 | 5/8 in | 22.2 mm | 22.2 mm | 37.8 mm | 6 | 84 | 5.7 kg |
| 13107 | 11/16 in | 23.8 mm | 23.8 mm | 37.8 mm | 6 | 72 | 5.8 kg |
| 13108 | 3/4 in | 25.9 mm | 25.9 mm | 37.8 mm | 6 | 72 | 6.1 kg |
| 13109 | 13/16 in | 27.9 mm | 27.9 mm | 37.8 mm | 4 | 48 | 5.2 kg |
| 13110 | 7/8 in | 29.9 mm | 29.9 mm | 37.8 mm | 4 | 48 | 5.9 kg |
| 13111 | 15/16 in | 31.9 mm | 31.9 mm | 37.8 mm | 4 | 48 | 6.5 kg |
| 13112 | 1 in | 33.9 mm | 33.9 mm | 40 mm | 4 | 48 | 7.7 kg |
| 13113 | 1-1/16 in | 35.9 mm | 35.9 mm | 40 mm | 4 | 48 | 8.7 kg |
| 13114 | 1-1/8 in | 37.9 mm | 37.9 mm | 42 mm | 4 | 48 | 9.9 kg |
| 13115 | 1-1/4 in | 41.9 mm | 41.9 mm | 42 mm | 2 | 24 | 6 kg |



ANSI B107.1



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability


! These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive 6 Point SAE Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|---------|
| 13201 | 3/8 in | 22 mm | 14.5 mm | 77 mm | 6 | 72 | 7.5 kg |
| 13202 | 7/16 in | 22 mm | 17 mm | 77 mm | 6 | 72 | 8.2 kg |
| 13203 | 1/2 in | 22 mm | 18.6 mm | 77 mm | 6 | 72 | 8.6 kg |
| 13204 | 9/16 in | 22 mm | 20.6 mm | 77 mm | 6 | 72 | 8.9 kg |
| 13205 | 5/8 in | 22 mm | 22 mm | 77 mm | 6 | 72 | 8.9 kg |
| 13206 | 11/16 in | 23.7 mm | 23.7 mm | 77 mm | 6 | 72 | 10.5 kg |
| 13207 | 3/4 in | 25.8 mm | 25.8 mm | 77 mm | 6 | 72 | 12.4 kg |
| 13208 | 13/16 in | 27.8 mm | 27.8 mm | 77 mm | 4 | 48 | 10.1 kg |
| 13209 | 7/8 in | 29.8 mm | 29.8 mm | 77 mm | 4 | 48 | 11.3 kg |
| 13210 | 15/16 in | 31.8 mm | 31.8 mm | 77 mm | 4 | 48 | 12.2 kg |
| 13211 | 1 in | 33.8 mm | 33.8 mm | 77 mm | 4 | 48 | 14.7 kg |
| 13212 | 1-1/16 in | 35.8 mm | 35.8 mm | 77 mm | 4 | 48 | 17 kg |
| 13213 | 1-1/8 in | 37.8 mm | 37.8 mm | 77 mm | 4 | 48 | 18.6 kg |
| 13214 | 1-1/4 in | 41.8 mm | 41.8 mm | 77 mm | 2 | 24 | 10.3 kg |



ANSI B107.1




- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

! These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive 6 Point Metric Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13319 | 8 mm | 22.2 mm | 13.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13320 | 9 mm | 22.2 mm | 14.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13301 | 10 mm | 22.2 mm | 15.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13302 | 11 mm | 22.2 mm | 16.5 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13303 | 12 mm | 22.2 mm | 17.8 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13304 | 13 mm | 22.2 mm | 19 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13305 | 14 mm | 22.2 mm | 20.3 mm | 38 mm | 6 | 84 | 5.4 kg |
| 13306 | 15 mm | 22.2 mm | 22.2 mm | 38 mm | 6 | 84 | 5.7 kg |
| 13307 | 16 mm | 22.2 mm | 22.2 mm | 38 mm | 6 | 84 | 5.7 kg |
| 13308 | 17 mm | 23.9 mm | 23.9 mm | 38 mm | 6 | 72 | 5.8 kg |
| 13309 | 18 mm | 24.9 mm | 24.9 mm | 38 mm | 6 | 72 | 6.1 kg |
| 13310 | 19 mm | 25.9 mm | 25.9 mm | 38 mm | 6 | 72 | 6.1 kg |
| 13311 | 20 mm | 27.8 mm | 27.8 mm | 38 mm | 4 | 48 | 5.2 kg |
| 13312 | 21 mm | 27.9 mm | 27.9 mm | 38 mm | 4 | 48 | 5.9 kg |
| 13313 | 22 mm | 29.9 mm | 29.9 mm | 38 mm | 4 | 48 | 5.9 kg |
| 13314 | 23 mm | 31.9 mm | 31.9 mm | 38 mm | 4 | 48 | 6.5 kg |
| 13315 | 24 mm | 31.9 mm | 31.9 mm | 38 mm | 4 | 48 | 6.5 kg |
| 13326 | 26 mm | 33.9 mm | 33.9 mm | 40 mm | 4 | 48 | 7.6 kg |
| 13316 | 27 mm | 35.9 mm | 35.9 mm | 40 mm | 4 | 48 | 8.7 kg |
| 13324 | 28 mm | 37.6 mm | 37.6 mm | 40 mm | 4 | 48 | 9.0 mm |
| 13317 | 30 mm | 39.9 mm | 39.9 mm | 42 mm | 2 | 24 | 5.2 kg |
| 13318 | 32 mm | 41.9 mm | 41.9 mm | 42 mm | 2 | 24 | 6.1 kg |
| 13321 | 34 mm | 43.9 mm | 43.9 mm | 43 mm | 2 | 24 | 7.6 kg |

ANSI B107.5M
DIN 3124



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

! These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive 6 Point Metric Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|---------|
| 13401 | 10 mm | 22 mm | 15.3 mm | 77 mm | 6 | 72 | 7.5 kg |
| 13402 | 11 mm | 22 mm | 16.5 mm | 77 mm | 6 | 72 | 8.2 kg |
| 13403 | 12 mm | 22 mm | 17.8 mm | 77 mm | 6 | 72 | 8.6 kg |
| 13404 | 13 mm | 22 mm | 19 mm | 77 mm | 6 | 72 | 8.6 kg |
| 13405 | 14 mm | 22 mm | 20.3 mm | 77 mm | 6 | 72 | 8.9 kg |
| 13406 | 15 mm | 22 mm | 21.4 mm | 77 mm | 6 | 72 | 8.9 kg |
| 13407 | 16 mm | 22 mm | 22 mm | 77 mm | 6 | 72 | 8.9 kg |
| 13408 | 17 mm | 23.8 mm | 23.8 mm | 77 mm | 6 | 72 | 10.5 kg |
| 13409 | 18 mm | 24.8 mm | 24.8 mm | 77 mm | 6 | 72 | 12.4 kg |
| 13410 | 19 mm | 25.8 mm | 25.8 mm | 77 mm | 6 | 72 | 12.4 kg |
| 13411 | 20 mm | 27.8 mm | 27.8 mm | 77 mm | 4 | 48 | 10.1 kg |
| 13412 | 21 mm | 27.8 mm | 27.8 mm | 77 mm | 4 | 48 | 10.1 kg |
| 13413 | 22 mm | 29.8 mm | 29.8 mm | 77 mm | 4 | 48 | 11.3 kg |
| 13414 | 24 mm | 31.8 mm | 31.8 mm | 77 mm | 4 | 48 | 12.2 kg |
| 13415 | 27 mm | 35.8 mm | 35.8 mm | 77 mm | 4 | 48 | 17 kg |
| 13416 | 30 mm | 39.8 mm | 39.8 mm | 77 mm | 2 | 24 | 9.5 kg |
| 13417 | 32 mm | 41.8 mm | 41.8 mm | 77 mm | 2 | 24 | 10.3 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.




ANSI B107.5M
DIN 3124

1/2" Drive 12 Point SAE Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13501 | 5/16 in | 22.2 mm | 12.5 mm | 37.8 mm | 6 | 84 | 4.9 kg |
| 13502 | 3/8 in | 22.2 mm | 14.5 mm | 37.8 mm | 6 | 84 | 4.9 kg |
| 13503 | 7/16 in | 22.2 mm | 17 mm | 37.8 mm | 6 | 84 | 5.2 kg |
| 13504 | 1/2 in | 22.2 mm | 18.6 mm | 37.8 mm | 6 | 84 | 5.2 kg |
| 13505 | 9/16 in | 22.2 mm | 20.6 mm | 37.8 mm | 6 | 84 | 5.4 kg |
| 13506 | 5/8 in | 22.2 mm | 22.2 mm | 37.8 mm | 6 | 84 | 5.7 kg |
| 13507 | 11/16 in | 23.8 mm | 23.8 mm | 37.8 mm | 6 | 72 | 5.8 kg |
| 13508 | 3/4 in | 25.9 mm | 25.9 mm | 37.8 mm | 6 | 72 | 6.1 kg |
| 13509 | 13/16 in | 27.9 mm | 27.9 mm | 37.8 mm | 4 | 48 | 5.2 kg |
| 13510 | 7/8 in | 29.9 mm | 29.9 mm | 37.8 mm | 4 | 48 | 5.9 kg |
| 13511 | 15/16 in | 31.9 mm | 31.9 mm | 37.8 mm | 4 | 48 | 6.5 kg |
| 13512 | 1 in | 33.9 mm | 33.9 mm | 40 mm | 4 | 48 | 7.7 kg |
| 13513 | 1-1/16 in | 35.9 mm | 35.9 mm | 40 mm | 4 | 48 | 8.7 kg |
| 13514 | 1-1/8 in | 37.9 mm | 37.9 mm | 42 mm | 4 | 48 | 9.9 kg |
| 13515 | 1-1/4 in | 41.9 mm | 41.9 mm | 42 mm | 2 | 24 | 6.1 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.




ANSI B107.1

1/2" Drive 12 Point Metric Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13619 | 8 mm | 22.2 mm | 13.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13620 | 9 mm | 22.2 mm | 14.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13601 | 10 mm | 22.2 mm | 15.3 mm | 38 mm | 6 | 84 | 4.9 kg |
| 13602 | 11 mm | 22.2 mm | 16.5 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13603 | 12 mm | 22.2 mm | 17.8 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13604 | 13 mm | 22.2 mm | 19 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13605 | 14 mm | 22.2 mm | 20.3 mm | 38 mm | 6 | 84 | 5.4 kg |
| 13606 | 15 mm | 22.2 mm | 22.2 mm | 38 mm | 6 | 84 | 5.8 kg |
| 13607 | 16 mm | 22.2 mm | 22.2 mm | 38 mm | 6 | 84 | 5.8 kg |
| 13608 | 17 mm | 23.9 mm | 23.9 mm | 38 mm | 6 | 72 | 5.8 kg |
| 13609 | 18 mm | 24.9 mm | 24.9 mm | 38 mm | 6 | 72 | 6.1 kg |
| 13610 | 19 mm | 25.9 mm | 25.9 mm | 38 mm | 6 | 72 | 6.1 kg |
| 13611 | 20 mm | 27.8 mm | 27.8 mm | 38 mm | 4 | 48 | 5.2 kg |
| 13612 | 21 mm | 27.9 mm | 27.9 mm | 38 mm | 4 | 48 | 5.9 kg |
| 13613 | 22 mm | 29.9 mm | 29.9 mm | 38 mm | 4 | 48 | 5.9 kg |
| 13614 | 23 mm | 31.9 mm | 31.9 mm | 38 mm | 4 | 48 | 6.5 kg |
| 13615 | 24 mm | 31.9 mm | 31.9 mm | 38 mm | 4 | 48 | 6.5 kg |
| 13616 | 27 mm | 35.9 mm | 35.9 mm | 40 mm | 4 | 48 | 8.7 kg |
| 13617 | 30 mm | 39.9 mm | 39.9 mm | 42 mm | 2 | 24 | 5.2 kg |
| 13618 | 32 mm | 41.9 mm | 41.9 mm | 42 mm | 2 | 24 | 6.1 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.




ANSI B107.5M
DIN 3124

1/2" Drive 12 Point Metric Deep Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13810 | 10 mm | 22 mm | 15.3 mm | 77 mm | 6 | 84 | 4.9 kg |
| 13812 | 12 mm | 22 mm | 17.8 mm | 77 mm | 6 | 84 | 4.9 kg |
| 13813 | 13 mm | 22 mm | 19 mm | 77 mm | 6 | 84 | 4.9 kg |
| 13814 | 14 mm | 22 mm | 20.3 mm | 77 mm | 6 | 84 | 5.2 kg |
| 13816 | 16 mm | 22 mm | 22 mm | 77 mm | 6 | 84 | 5.2 kg |
| 13817 | 17 mm | 23.8 mm | 23.8 mm | 77 mm | 6 | 84 | 5.2 kg |
| 13818 | 18 mm | 24.8 mm | 24.8 mm | 77 mm | 6 | 84 | 5.2 kg |
| 13819 | 19 mm | 25.8 mm | 25.8 mm | 77 mm | 6 | 84 | 5.4 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.



ANSI B107.5M
DIN 3124

1/2" Drive External Torx® Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|---|----|--------|
| 13701 | E10 | 22 mm | 13 mm | 38 mm | 6 | 84 | 5.2 kg |
| 13702 | E12 | 22 mm | 15 mm | 38 mm | 6 | 84 | 5.4 kg |
| 13703 | E14 | 22 mm | 17 mm | 38 mm | 6 | 84 | 5.7 kg |
| 13704 | E16 | 22 mm | 19 mm | 38 mm | 6 | 84 | 5.7 kg |
| 13705 | E18 | 23.8 mm | 21 mm | 38 mm | 6 | 72 | 6.1 kg |
| 13706 | E18 | 25.8 mm | 23.5 mm | 38 mm | 4 | 48 | 5.9 kg |
| 13707 | E22 | 25.8 mm | 25.8 mm | 38 mm | 4 | 48 | 6.5 kg |
| 13708 | E24 | 27.8 mm | 27.8 mm | 40 mm | 4 | 48 | 6.5 kg |

- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology: Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

⚠ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.



1/2" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13971 | 250 mm | 4 | 24 | 12.8 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/2" Drive Quick-Release Round Head Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13901 | 244 mm | 4 | 24 | 15.8 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

1/2" Drive Quick-Release Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13972 | 250 mm | 4 | 24 | 14.8 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/2" Drive Quick-Release Stubby Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13960 | 140 mm | 6 | 24 | 10.4 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/2" Drive Heavy Duty Offset Quick-Release Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13970 | 261 mm | 4 | 24 | 14.8 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Convenient single hand direction change switch
- Quick-release capability to easily eject an engaged socket even under slippery conditions

1/2" Drive Wobble Extensions

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|-------|----------------|---|----|---------|
| 13904 | 5 in | 125 mm | 4 | 24 | 6.2 kg |
| 13905 | 10 in | 250 mm | 4 | 24 | 11.3 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

1/2" Drive Locking Extensions

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|-------|----------------|---|-----|---------|
| 13906 | 3 in | 75 mm | 4 | 120 | 26.7 kg |
| 13907 | 5 in | 125 mm | 4 | 24 | 6.6 kg |
| 13908 | 10 in | 250 mm | 4 | 24 | 12.9 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Flex Handle / Breaker Bar

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13909 | 250 mm | 4 | 24 | 14.7 kg |
| 13911 | 375 mm | 4 | 16 | 19.4 kg |
| 13951 | 432 mm | 4 | 24 | 22.9 kg |
| 13952 | 610 mm | 4 | 24 | 27.2 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Direction change function

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive T-handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13910 | 250 mm | 4 | 24 | 11.7 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Universal Joint

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|--------|
| 13912 | 1/2" | 1/2" | 68.2 mm | 4 | 48 | 8.3 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Adapters

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|-----|---------|
| 13913 | 1/2" | 3/8" | 35.1 mm | 4 | 56 | 9.2 kg |
| 13950 | 1/2" | 3/4" | 35.1 mm | 4 | 120 | 15.4 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Bits Adapter

| Cat. No. | Size | | | G.W. |
|----------|---------|---|----|--------|
| 13914 | 5/16 in | 6 | 72 | 8.1 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Metric Spark Plug Sockets

| Cat. No. | Fastener Size | | | G.W. |
|----------|---------------|---|----|---------|
| 13915 | 16 mm | 4 | 72 | 10.5 kg |
| 13916 | 21 mm | 4 | 80 | 18.6 kg |

ANSI B107.34M



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive SAE Spark Plug Sockets

| Cat. No. | Fastener Size | | | G.W. |
|----------|---------------|---|----|---------|
| 13917 | 5/8 in | 4 | 48 | 7.1 kg |
| 13918 | 13/16 in | 4 | 48 | 11.3 kg |

ANSI B107.34M



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Offset Handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 13919 | 260 mm | 4 | 24 | 11.5 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

1/2" Drive 3-Way Adapter

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|--------|
| 13930 | 1/2" | 3/8" | 43.6 mm | 4 | 56 | 6.4 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

Warning: These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

1/2" Drive Speeder Handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 17001 | 410 mm | 6 | 12 | 15.4 kg |


ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

3/4" Drive 12 Point SAE Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|----|---------|
| 16501 | 3/4 in | 38 mm | 29.5 mm | 49.5 mm | 10 | 60 | 13.6 kg |
| 16502 | 13/16 in | 38 mm | 31.5 mm | 49.5 mm | 10 | 60 | 13.6 kg |
| 16503 | 7/8 in | 38 mm | 32.5 mm | 49.5 mm | 10 | 60 | 13.6 kg |
| 16504 | 15/16 in | 38 mm | 34.5 mm | 49.5 mm | 10 | 60 | 13.6 kg |
| 16505 | 1 in | 38.2 mm | 35 mm | 50 mm | 10 | 60 | 13.6 kg |
| 16506 | 1-1/16 in | 38 mm | 38.2 mm | 52 mm | 10 | 60 | 13.6 kg |
| 16507 | 1-1/8 in | 38 mm | 39.2 mm | 52 mm | 8 | 48 | 12.5 kg |
| 16508 | 1-3/16 in | 38 mm | 42.2 mm | 54 mm | 8 | 48 | 13.5 kg |
| 16509 | 1-1/4 in | 38 mm | 44.2 mm | 56 mm | 6 | 36 | 11.8 kg |
| 16510 | 1-5/16 in | 38 mm | 46.2 mm | 56 mm | 6 | 36 | 12.9 kg |
| 16511 | 1-3/8 in | 42 mm | 48.2 mm | 56 mm | 6 | 36 | 14 kg |
| 16512 | 1-7/16 in | 42 mm | 50.2 mm | 58 mm | 6 | 36 | 15.4 kg |
| 16513 | 1-1/2 in | 45 mm | 52.2 mm | 60 mm | 4 | 24 | 12 kg |
| 16520 | 1-9/16 in | 45 mm | 53.5 mm | 60 mm | 4 | 24 | 13.1 kg |
| 16514 | 1-5/8 in | 45 mm | 56 mm | 64 mm | 4 | 24 | 14.2 kg |
| 16515 | 1-11/16 in | 48 mm | 57 mm | 64 mm | 4 | 24 | 15 kg |
| 16516 | 1-3/4 in | 48 mm | 60.5 mm | 66 mm | 4 | 16 | 10.6 kg |
| 16517 | 1-13/16 in | 48 mm | 62 mm | 68 mm | 4 | 16 | 9.7 kg |
| 16518 | 1-7/8 in | 48 mm | 63.5 mm | 70 mm | 2 | 12 | 9.7 kg |
| 16519 | 2 in | 48 mm | 68 mm | 72 mm | 2 | 12 | 10.3 kg |
| 16521 | 2-1/16 in | 48 mm | 70.5 mm | 74 mm | 2 | 8 | 7.5 kg |
| 16522 | 2-1/8 in | 48 mm | 72 mm | 74 mm | 2 | 8 | 8.1 kg |
| 16523 | 2-1/4 in | 48 mm | 76 mm | 76 mm | 2 | 8 | 8.7 kg |

ANSI B107.5M
DIN 3124



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability



These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive 12 Point Metric Standard Length Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. B: Wrench End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|--------------------|------------------------|----|----|---------|
| 16602 | 19 mm | 38 mm | 28.5 mm | 47.5 mm | 10 | 60 | 13.8 kg |
| 16603 | 21 mm | 38 mm | 31.5 mm | 49.5 mm | 10 | 60 | 13.8 kg |
| 16604 | 22 mm | 38 mm | 32.5 mm | 49.5 mm | 10 | 60 | 13.8 kg |
| 16605 | 23 mm | 38 mm | 33.5 mm | 49.5 mm | 10 | 60 | 13.8 kg |
| 16606 | 24 mm | 38 mm | 34.5 mm | 49.5 mm | 10 | 60 | 13.8 kg |
| 16607 | 25 mm | 38.2 mm | 35 mm | 50 mm | 10 | 60 | 13.8 kg |
| 16608 | 26 mm | 38 mm | 37.2 mm | 50 mm | 10 | 60 | 13.8 kg |
| 16609 | 27 mm | 38 mm | 38.2 mm | 52 mm | 10 | 60 | 13.8 kg |
| 16610 | 28 mm | 38 mm | 39.2 mm | 52 mm | 8 | 48 | 12 kg |
| 16611 | 29 mm | 38 mm | 40.2 mm | 52 mm | 8 | 48 | 12.5 kg |
| 16612 | 30 mm | 38 mm | 42.2 mm | 54 mm | 8 | 48 | 13.5 kg |
| 16613 | 32 mm | 38 mm | 44.2 mm | 56 mm | 6 | 36 | 11.1 kg |
| 16614 | 33 mm | 38 mm | 46.2 mm | 56 mm | 6 | 36 | 12.2 kg |
| 16615 | 34 mm | 38 mm | 47.2 mm | 56 mm | 6 | 36 | 12.9 kg |
| 16616 | 35 mm | 42 mm | 48.2 mm | 56 mm | 6 | 36 | 14 kg |
| 16617 | 36 mm | 42 mm | 50.2 mm | 58 mm | 6 | 36 | 15.4 kg |
| 16618 | 38 mm | 45 mm | 52.2 mm | 60 mm | 4 | 24 | 12 kg |
| 16619 | 41 mm | 45 mm | 56 mm | 64 mm | 4 | 24 | 14.2 kg |
| 16620 | 46 mm | 48 mm | 62 mm | 68 mm | 4 | 16 | 11.3 kg |
| 16622 | 50 mm | 48 mm | 68 mm | 72 mm | 2 | 12 | 10.3 kg |
| 16623 | 55 mm | 48 mm | 74 mm | 76 mm | 2 | 12 | 12.6 kg |
| 16624 | 60 mm | 48 mm | 80 mm | 78 mm | 2 | 12 | 13.2 kg |

ANSI B107.5M
DIN 3124


- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology- Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability



These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

Socket & Drive Tool-Open Stock

3/4" Drive Quick-Release Teardrop Ratchet

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|---|---------|
| 16901 | 500 mm | 1 | 8 | 20.4 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

3/4" Drive T-handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 16905 | 450 mm | 1 | 24 | 35.6 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive Universal Joint

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|---------|
| 16907 | 3/4" | 3/4" | 75.2 mm | 3 | 18 | 11.6 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive Standard Extension Bar

| Cat. No. | Size | Overall Length | | | G.W. |
|----------|-------|----------------|---|----|---------|
| 16902 | 4 in | 100 mm | 6 | 36 | 15.6 kg |
| 16903 | 8 in | 200 mm | 3 | 18 | 13.8 kg |
| 16904 | 16 in | 400 mm | 2 | 12 | 9.3 kg |

ANSI B107.10M
DIN 3123



- Made of Chrome Vanadium steel
- Direction change function
- Push in for standard extension bar

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive Flex Handle / Breaker Bar

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|---|---------|
| 16906 | 450 mm | 1 | 9 | 17.9 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel
- Direction change function

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive Adapter

| Cat. No. | Female Drive Size | Male Drive Size | Overall Length | | | G.W. |
|----------|-------------------|-----------------|----------------|---|----|--------|
| 16908 | 3/4" | 1/2" | 35.1 mm | 6 | 36 | 8.4 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

⚠ These sockets accessories should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/4" Drive Offset Handle

| Cat. No. | Overall Length | | | G.W. |
|----------|----------------|---|----|---------|
| 16919 | 380 mm | 4 | 24 | 25.6 kg |

ANSI B107.10M
DIN 3122



- Made of Chrome Vanadium steel

1/4" Drive Torx® Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|----|-----|--------|
| 21101 | T8 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21102 | T10 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21103 | T15 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21104 | T20 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21105 | T25 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21108 | T27 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21106 | T30 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |
| 21107 | T40 | 12 mm | 36.5 mm | 12 | 144 | 3.6 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/4" Drive Metric Hex Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|----|-----|---------|
| 21201 | 3 mm | 12 mm | 36.5 mm | 12 | 396 | 8.7 kg |
| 21202 | 4 mm | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21203 | 5 mm | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21204 | 6 mm | 12 mm | 36.5 mm | 12 | 396 | 9.8 kg |
| 21206 | 7 mm | 12 mm | 36.5 mm | 12 | 396 | 10.3 kg |
| 21205 | 8 mm | 12 mm | 36.5 mm | 12 | 396 | 10.3 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/4" Drive Phillips Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|----|-----|--------|
| 21301 | #1 | 12 mm | 36.5 mm | 12 | 396 | 8.7 kg |
| 21302 | #2 | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21303 | #3 | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/4" Drive Pozidriv Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|----|-----|--------|
| 21401 | #1 | 12 mm | 36.5 mm | 12 | 396 | 8.7 kg |
| 21402 | #2 | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21403 | #3 | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Metric Hex Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 22201 | 3 mm | 18 mm | 48 mm | 6 | 198 | 8.9 kg |
| 22202 | 4 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22203 | 5 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22204 | 6 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22205 | 7 mm | 18 mm | 48 mm | 6 | 198 | 9.8 kg |
| 22206 | 8 mm | 18 mm | 48 mm | 6 | 198 | 10.9 kg |
| 22207 | 10 mm | 18 mm | 48 mm | 6 | 198 | 12 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Phillips Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|--------|
| 22301 | #1 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22302 | #2 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22303 | #3 | 18 mm | 48 mm | 6 | 198 | 9.5 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/4" Drive Slotted Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|----|-----|--------|
| 21501 | 4 mm | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21502 | 5.5 mm | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |
| 21503 | 6.5 mm | 12 mm | 36.5 mm | 12 | 396 | 9.2 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Torx® Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 22101 | T10 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22102 | T15 | 18 mm | 48 mm | 6 | 198 | 8.9 kg |
| 22103 | T20 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22104 | T25 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22105 | T27 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22106 | T30 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22107 | T40 | 18 mm | 48 mm | 6 | 198 | 9.5 kg |
| 22108 | T45 | 18 mm | 48 mm | 6 | 198 | 10 kg |
| 22109 | T50 | 18 mm | 48 mm | 6 | 198 | 10.6 kg |
| 22110 | T55 | 18 mm | 48 mm | 6 | 198 | 11.4 kg |
| 22111 | T60 | 18 mm | 48 mm | 6 | 198 | 11.7 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Pozidriv Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|--------|
| 22401 | #1 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22402 | #2 | 18 mm | 48 mm | 6 | 198 | 9.5 kg |
| 22403 | #3 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Slotted Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|--------|
| 22504 | 4 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22501 | 5.5 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22502 | 6.5 mm | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22503 | 8 mm | 18 mm | 48 mm | 6 | 198 | 9.8 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

3/8" Drive Torx® Tamper Proof Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 22601 | T45 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22602 | T50 | 18 mm | 48 mm | 6 | 198 | 9.2 kg |
| 22603 | T55 | 18 mm | 48 mm | 6 | 198 | 9.6 kg |
| 22604 | T60 | 18 mm | 48 mm | 6 | 198 | 11.4 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Torx® Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 24101 | T20 | 24 mm | 75 mm | 6 | 180 | 14.1 kg |
| 24102 | T25 | 24 mm | 75 mm | 6 | 180 | 14.3 kg |
| 24103 | T27 | 24 mm | 75 mm | 6 | 180 | 14.6 kg |
| 24104 | T30 | 24 mm | 75 mm | 6 | 180 | 15 kg |
| 24105 | T40 | 24 mm | 75 mm | 6 | 180 | 15.3 kg |
| 24106 | T45 | 24 mm | 75 mm | 6 | 180 | 16.4 kg |
| 24107 | T50 | 24 mm | 75 mm | 6 | 180 | 16.4 kg |
| 24108 | T55 | 24 mm | 75 mm | 6 | 180 | 17.1 kg |
| 24109 | T60 | 24 mm | 75 mm | 6 | 180 | 22.2 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Triple Square Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 24801 | M5 | 24 mm | 75 mm | 6 | 180 | 14.3 kg |
| 24802 | M6 | 24 mm | 75 mm | 6 | 180 | 14.5 kg |
| 24803 | M8 | 24 mm | 75 mm | 6 | 180 | 14.9 kg |
| 24804 | M10 | 24 mm | 75 mm | 6 | 180 | 16.8 kg |
| 24805 | M12 | 24 mm | 75 mm | 6 | 180 | 21.8 kg |
| 24806 | M14 | 24 mm | 75 mm | 6 | 180 | 22.2 kg |
| 24807 | M16 | 24 mm | 75 mm | 6 | 180 | 23.6 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Long Torx® Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|----|---------|
| 25101 | T20 | 24 mm | 125 mm | 6 | 72 | 7.3 kg |
| 25102 | T25 | 24 mm | 125 mm | 6 | 72 | 7.4 kg |
| 25103 | T27 | 24 mm | 125 mm | 6 | 72 | 7.5 kg |
| 25104 | T30 | 24 mm | 125 mm | 6 | 72 | 7.7 kg |
| 25105 | T40 | 24 mm | 125 mm | 6 | 72 | 7.8 kg |
| 25106 | T45 | 24 mm | 125 mm | 6 | 72 | 7.9 kg |
| 25107 | T50 | 24 mm | 125 mm | 6 | 72 | 8 kg |
| 25108 | T55 | 24 mm | 125 mm | 6 | 72 | 9 kg |
| 25109 | T60 | 24 mm | 125 mm | 6 | 72 | 13.3 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Metric Hex Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 24201 | 4 mm | 24 mm | 75 mm | 6 | 180 | 14.3 kg |
| 24202 | 5 mm | 24 mm | 75 mm | 6 | 180 | 14.6 kg |
| 24203 | 6 mm | 24 mm | 75 mm | 6 | 180 | 15.3 kg |
| 24204 | 7 mm | 24 mm | 75 mm | 6 | 180 | 16.1 kg |
| 24205 | 8 mm | 24 mm | 75 mm | 6 | 180 | 16.2 kg |
| 24206 | 10 mm | 24 mm | 75 mm | 6 | 180 | 17.3 kg |
| 24207 | 12 mm | 24 mm | 75 mm | 6 | 180 | 22.9 kg |
| 24208 | 14 mm | 24 mm | 75 mm | 6 | 180 | 23.8 kg |
| 24209 | 17 mm | 24 mm | 75 mm | 6 | 180 | 25.6 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive SAE Hex Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|-----|---------|
| 24401 | 1/4 in | 24 mm | 55 mm | 6 | 180 | 16.1 kg |
| 24402 | 5/16 in | 24 mm | 55 mm | 6 | 180 | 16.2 kg |
| 24403 | 3/8 in | 24 mm | 55 mm | 6 | 180 | 17.3 kg |
| 24404 | 7/16 in | 24 mm | 55 mm | 6 | 180 | 20.4 kg |
| 24405 | 1/2 in | 24 mm | 55 mm | 6 | 180 | 22.9 kg |
| 24406 | 9/16 in | 24 mm | 55 mm | 6 | 180 | 23.8 kg |
| 24407 | 5/8 in | 24 mm | 55 mm | 6 | 180 | 25.6 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Metric Long Hex Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|----|---------|
| 25201 | 4 mm | 24 mm | 125 mm | 6 | 72 | 7.6 kg |
| 25202 | 5 mm | 24 mm | 125 mm | 6 | 72 | 7.6 kg |
| 25203 | 6 mm | 24 mm | 125 mm | 6 | 72 | 7.5 kg |
| 25204 | 7 mm | 24 mm | 125 mm | 6 | 72 | 7.8 kg |
| 25205 | 8 mm | 24 mm | 125 mm | 6 | 72 | 8 kg |
| 25206 | 10 mm | 24 mm | 125 mm | 6 | 72 | 9.5 kg |
| 25207 | 12 mm | 24 mm | 125 mm | 6 | 72 | 13.4 kg |
| 25208 | 14 mm | 24 mm | 125 mm | 6 | 72 | 14 kg |
| 25209 | 17 mm | 24 mm | 125 mm | 6 | 72 | 16.7 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.

1/2" Drive Long Triple Square Bit Sockets

| Cat. No. | Fastener Size | Dim. A: Drive End | Dim. C: Overall Length | | | G.W. |
|----------|---------------|-------------------|------------------------|---|----|---------|
| 25801 | M5 | 24 mm | 125 mm | 6 | 72 | 7.2 kg |
| 25802 | M6 | 24 mm | 125 mm | 6 | 72 | 7.4 kg |
| 25803 | M8 | 24 mm | 125 mm | 6 | 72 | 7.7 kg |
| 25804 | M10 | 24 mm | 125 mm | 6 | 72 | 8.8 kg |
| 25805 | M12 | 24 mm | 125 mm | 6 | 72 | 13.3 kg |
| 25806 | M14 | 24 mm | 125 mm | 6 | 72 | 13.4 kg |
| 25807 | M16 | 24 mm | 125 mm | 6 | 72 | 16.1 kg |



- Professional, S2 material, Full Polish Chrome
- Heat Treated Socket Bases for Durability and Serviceability

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders. Nature of this product is subject to wear and tear upon usage. Not covered under Lifetime Warranty.